Cheatography

Webstrix Functions Cheat Sheet

by Mathieu Green (mathieu.green) via cheatography.com/35613/cs/11188/

Framework function

getURL()	Give the URL of the website, this url come from the configuration file.
getProjectPath()	Give the full path of the project from the root.
getAllFolderAndSub-Folder($path)	Give all folders and subfolders from the path given.
getAllFolderAndPat-hFromPath($path)	Give all folder and path of the path given
getAllFolderFromPa-th($path)	Give all folder of the path given

Session function - new session();

- creeUneSessionPourUtilisateur($idUtilisateur, $timeLifeSeconde)
- nettoyerSession()
- verifierSessionExistanteAvecClefUnique($uniqueKeySession, $ip)
- getSessionIdUtilisateur($uniqueKeySession)
- getIdUtilisateurActuel()
- deleteSessionServeurPourUtilisateur($idUtilisateur)
- detruireSessionBrowserPourUtilisateur()
- verifierSessionExpire()
- verifierSessionExistanteSurLeBrowser()
- getSessionKey()
- setVariablePourUtilisateurAvecClef($nomDeLaVariable, $value, $clef)
- __set($nomDeLaVariable, $value)
- __get($nomDeLaVariable)

Core Controller function - CoreController();

- chargerControleur($nomDuControlleur)
- ajouterView($view = null, $variables = null)

Database function - new db() ;

last_i-nse-rt_id()	get the latest id insert in the DB
query(-$query)	Inject a query inside mysql, return false on fail, a list of elements or true when well done

- getListAsArray($table, $options = null)
- getRow($query)
- insertArrayElements($table = null, $listElements = null, $listValues = null, $options = null)
- updateArrayElements($table = null, $listElements = null, $listValues = null, $option = null)
- deleteRowById($table, $id)



By **Mathieu Green**
(mathieu.green)
cheatography.com/mathieu-green/
www.webstrix.ca

Not published yet.
Last updated 31st March, 2017.

Sponsored by **Readable.com**
Measure your website readability!
https://readable.com