

Framework function

getURL()	Give the URL of the website, this url come from the configuration file.
getProjectPath()	Give the full path of the project from the root.
getAllFolderAndSubFolder(\$path)	Give all folders and subfolders from the path given.
getAllFolderAndPathFromPath(\$path)	Give all folder and path of the path given
getAllFolderFromPath(\$path)	Give all folder of the path given

Session function - new session();

creerUneSessionPourUtilisateur(\$idUtilisateur, \$timeLifeSeconde)
nettoyerSession()
verifierSessionExistanteAvecClefUnique(\$uniqueKeySession, \$ip)
getSessionIdUtilisateur(\$uniqueKeySession)
getIdUtilisateurActuel()
deleteSessionServeurPourUtilisateur(\$idUtilisateur)
detruiresessionBrowserPourUtilisateur()
verifierSessionExpire()
verifierSessionExistanteSurLeBrowser()
getSessionKey()
setVariablePourUtilisateurAvecClef(\$nomDeLaVariable, \$value, \$clef)
__set(\$nomDeLaVariable, \$value)
__get(\$nomDeLaVariable)

Core Controller function - CoreController();

chargerControleur(\$nomDuControlleur)
ajouterView(\$view = null, \$variables = null)

Database function - new db() ;

last_insert_id()	get the latest id insert in the DB
query(\$query)	Inject a query inside mysql, return false on fail, a list of elements or true when well done
getListAsArray(\$table, \$options = null)	
getRow(\$query)	
insertArrayElements(\$table = null, \$listElements = null, \$listValues = null, \$options = null)	
updateArrayElements(\$table = null, \$listElements = null, \$listValues = null, \$option = null)	
deleteRowById(\$table, \$id)	



By **Mathieu Green**

(mathieu.green)

cheatography.com/mathieu-green/

www.webstrix.ca

Not published yet.

Last updated 31st March, 2017.

Page 1 of 1.

Sponsored by **Readability-Score.com**

Measure your website readability!

<https://readability-score.com>