

Using Units

```
systemctl start unit
```

```
systemctl stop unit
```

```
systemctl restart unit
```

```
systemctl status unit
```

Units can be, for example, services (.service), mount points (.mount), devices (.device) or sockets (.socket).

Installing AUR packages

```
$ wget http://aur.archlinux.org/.../foo.tar.gz
```

Acquire the tarball with PKGBUILD

```
$ tar -xvf foo.tar.gz
```

Extract the tarball

```
$ makepkg -s
```

Create the package

```
$ vim src/README
```

Check for README in src/ for useful information

```
$ pacman -U /path/to/pkg.tar.tx
```

Install the resulting package with pacman

Adding unofficial repository

```
$ sudo vim /etc/pacman.conf
```

Add a new repository to the pacman configuration file. Interesting repositories can be found on the [wiki](#).

```
$ pacman-key -r keyid
```

Import the key.

```
$ pacman-key -f keyid
```

Verify the key (lists fingerprint for specified key).

```
$ pacman-key --lsign-key keyid
```

Locally sign the imported key.

You may first need to run *dirmngr* as root if you encounter the "Keyserver receive failed. Not dirmngr." error.



By **Mikero**
cheatography.com/mikero/

Not published yet.
Last updated 7th June, 2015.
Page 1 of 1.

Sponsored by **Readability-Score.com**
Measure your website readability!
<https://readability-score.com>