

Overview

pacman <operation> [options] [targets]

Operations

| | |
|----------------|---|
| -D, --database | Operate on the package database |
| -Q, --query | Query the package database |
| -R, --remove | Remove package(s) from the system |
| -S, --sync | Synchronize packages |
| -T, --deptest | Check dependencies |
| -U, --upgrade | Upgrade or add package(s) to the system |
| -F, --files | Query the files database |
| -V, --version | Display version and exit |
| -h, --help | Display syntax for the given operation |

Options

| | |
|------------------|--|
| -b, --dbpath | Specify an alternative database location |
| -r, --root | Specify an alternative installation root |
| -v, --verbose | Output paths such as as the Root, Conf File, DB Path, Cache Dirs |
| --arch <arch> | Specify an alternate architecture |
| --cachedir <dir> | Specify an alternative package cache location |
| --color <when> | Specify when to enable coloring |
| --config <file> | Specify an alternate configuration file |
| --debug | Display debug messages |

Options (cont)

| | |
|----------------------------|---|
| --gpgdir <dir> | Specify a directory of files used by GnuPG to verify package signatures |
| --hookdir <dir> | Specify an alternate directory containing hook files |
| --logfile <file> | Specify an alternate log file |
| --noconfirm | Bypass any and all "Are you sure?" messages |
| --confirm | Cancel the effects of a previous --noconfirm |
| --disable-download-timeout | Disable defaults for low speed limit and timeout on downloads |
| --sysroot <dir> | Specify an alternative system root |



By misterrabinhalder

cheatography.com/misterrabinhalder/

Not published yet.

Last updated 9th July, 2019.

Page 1 of 1.

Sponsored by CrosswordCheats.com

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>