

Errors

undefined function xxx_path/3 cannot use ^xxx outside of match clauses

add the resource to the router (resources "/xxx", xxxController)

add import Ecto.Query to the controller

hex.pm gotchas

password resets: when you forget a password and reset it, you have an option to revoke api keys, which is default, you must regenerate an api key via cli: mix hex.user auth

errors: inserted_at: can only modify a release up to one hour after creation if you get this error it is because you didnt update the current version within 1 hour, so you need to bump the version located in mix.exs

phoenix gotchas

to render a different view/template combo for a controller

```
conn
|> put_view(xxxWeb.xxxPartialsView)
|> render("xxx.html", assigns: assigns)
```

to not render templates for only certain controller actions

```
plug :put_layout, false when action in [:xxx, :yyy]
```

to render certain layout for only certain controller actions

```
:put_layout, {xxxWeb.xxxView, :layout}
when action in [:xxx, :yyy]
```

in order to use https, the config goes into xxxWeb/config/xxx.exs

Elixir Gotchas

to access a config

```
var config = Application.get_env(:my, :title)
```

ecto gotchas

cast_assoc/3 is only used in the changesets of schemas that have has_one or has_many. It invokes the cast/3 validation in the changeset of the associated schema.

assoc_constraint/3 is used in the changesets of schemas that have belongs_to. It checks to make sure the parent schema is in the database so an orphaned record isn't inserted.

foreign_key_constraint/3 is used similarly to assoc_constraint/3, except that it uses the database to validate the foreign key constraint, whereas assoc_constraint/3 uses the Ecto schema definition.

Brunch Gotchas

bundling stylesheets:

in phoenix 1.3 to bundle a custom directory it has to be both added to watched as well as the jointo under stylesheets the parent dir is app/assets and is implied

in this example we are bundling xxxweb/assets/bundled/page/*.css to xxxweb/priv/static/css/page/vendor.css

ex: for css

```
joinTo: {"css/page/vendor.css": /^bundled-V(?:cssV)?page/},
watched: ["static", "css", "js", "vendor", "bundled"]
```

for the js i typically separate what i want bundled into a bundled dir, we also need to include node_modules we do so like this.

ex for js.

```
"js/user/vendor.js": /^(bundledVjsVuser|vendor|deps|node_modules).*/
```

but we also need to join the main file responsible for importing the channels etc typically called app.js we do so by adding the path to this file to the modules:auto-require it is important to remember the path is pre compilation, (this took days to understand this) compiling like this.

ex.

```
modules: {
  autoRequire: {
    "js/user/vendor.js": ["bundled/js/user/app"],
```

Brunch Gotchas (cont)

```
}
},
```

