

SAP

Make sure to run these commands as `<sid>adm` user

Monitoring SAP instances

sapcontrol -nr <nr> -function GetSystemInstanceList

Shows all configured instances and their respective status

Starting and stopping SAP instances

sapcontrol -nr <nr> -function Start

Starts the given SAP instance

sapcontrol -nr <nr> -function Stop

Stops the given SAP instance

SAP log file locations

`/usr/sap/<SID>/<INSTANCE>/work/`

Workprocess and other log files

`/home/<sid>adm/[start|stop]sap_<INSTANCE>.log`

Startup and shutdown trace

Oracle

Make sure to run these commands as `ora<sid>` user

Monitoring Oracle instances

lsnrctl status

Displays the status of the Oracle listener

Starting the Oracle listener

lsnrctl start

Starts the Oracle listener

Oracle log file locations

`/oracle/<SID>/saptrace/diag/rdbms/<sid>/`

`<SID>/trace/alert_<SID>.log`

Oracle instance log

Cluster

Make sure to run these commands as `root` user

Monitoring the Cluster status

crm_mon -1Arfj

Displays the configured Cluster resources and their respective status

Manging cluster resources

crm resource start <name>

Starts the given resource

crm resource stop <name>

Stops the given resource

crm resource cleanup <name>

Removes a given resources failure state (and does a recheck)

Migrating Cluster resources

crm resource migrate <resource> PT<N>M

Forces a resource away from the current node for N minutes



By **MoepMan**

cheatography.com/moepman/

Not published yet.

Last updated 18th September, 2019.

Page 1 of 1.

Sponsored by **CrosswordCheats.com**

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>