

# vim tpope/vim-surround Cheat Sheet

by mutanclan (mutanclan) via cheatography.com/79625/cs/19320/

## Delete surroundings

ds	delete surrounding	
ds"	delete surrounding "	
ds)	delete surrounding ()	
dst	delete surrounding (html)tag	

#### Examples

### Visual mode

S" surround selected text with "

S surround selected text with ...

### Examples in visual mode

### **Targets**

The |ds| and |cs| commands both take a target as their first argument. The possible targets are based closely on the |text- obj ects| provided by Vim. All targets are currently just one character. (, ), {, }, [, ], <, and > The targets b, B, r, and a are aliases for ), }, ], and > A t is a pair of HTML or XML tags. The letters w, W, and scorrespond to a |word|, a |WORD|, and a |sente nce|. A p

represents a |parag raph|

## Change surroundings

cs"	change surrounding " to '	
cs"<-	change surrounding " to <q><b>some</b> text</q>	
cst	change surrounding tag with	
cs)]	change surrounding () to []	
cs)[	change surrounding () to [] with spaces	
Examples		

### Create surroundings

ysiw)	add surrounding () to inner word
yss]	add surrounding [] to whole line,
	without leading whitespace

### Examples

### functions

ysWfprint <cr></cr>	wraps old text into a function print
ysWFprint <cr></cr>	wraps a WORD into a function print with spaces



By **mutanclan** (mutanclan) cheatography.com/mutanclan/

Published 9th April, 2019. Last updated 9th April, 2019. Page 1 of 1. Sponsored by **Readable.com**Measure your website readability!
https://readable.com