

Delete surroundings

ds	delete surrounding
ds"	delete surrounding "
ds)	delete surrounding ()
dst	delete surrounding (html)tag

Examples

Visual mode

S"	surround selected text with "
S<p>	surround selected text with <p> ... </p>

Examples in visual mode

Targets

The |ds| and |cs| commands both take a target as their first argument. The possible targets are based closely on the |text-objects| provided by Vim.

All targets are currently just one character.

(,), {, }, [,], <, and >

The targets b, B, r, and a are aliases for), },], and >

', ", `,

A t is a pair of HTML or XML tags.

The letters w, W, and s correspond to a |word|, a |WORD|, and a |sentence|. A p represents a |paragraph|

Change surroundings

cs"	change surrounding " to '
cs"<-	change surrounding " to <q> some
q>	text </q>
cst<p>	change surrounding tag with <p>
cs)]	change surrounding () to []
cs)[change surrounding () to [] with spaces

Examples

Create surroundings

ysiW)	add surrounding () to inner word
yss]	add surrounding [] to whole line, without leading whitespace

Examples

functions

ysWfprint<cr>	wraps old text into a function print
ysWFprint<cr>	wraps a WORD into a function print with spaces



By **mutanclan** (mutanclan)
cheatography.com/mutanclan/

Published 9th April, 2019.
Last updated 9th April, 2019.
Page 1 of 1.

Sponsored by **Readable.com**
Measure your website readability!
<https://readable.com>