check_subscriber_active_to_service_group

input

msisdn, service_id

sql

```
select service_id,id from mt_subscribers where msisdn=? and active='y' and service_id=?
```

if(!$subscriber_id)

```
select service_id,id from mt_subscribers where msisdn=? and active='y' and service_id in(select id from services where service_group_id=?
```

return

$already_sub_service_id,$subscriber_id

get_mo_shortcode_based_on_service_id

input

service_id

sql

```
select mo_short_code from keywords where service_id=? limit 1
```

return: $mo_short_code

example: SyniverseNlg5

if (!$mo_short_code)

```
select k.mo_short_code from keywords k,carrier_service_override cor where cor.override_service_id=? and cor.incoming_service_id=k.service_id limit 1
```

get_messages_based_on_service

input

$service_id, $svc_msg_type_id

sql

```
select smm.id, smm.billed, smm.tpoa, smm.msg_priority, smm.sc_id, smm.credit_value, m.msg, mt.type, smt.svc_type, smm.delay, smm.delay_minutes from service_msg_matrix smm, messages m, messages_type mt, service_msg_type smt where smm.service_id=? and smm.svc_msg_type_id in($svc_msg_type_id) and smm.msg_id=m.id and m.msg_type_id=mt.id and smm.svc_msg_type_id=smt.id order by smm.
```

return: $sth_msg

statement to the sql command

checkcheck_shortcode_overide

purpose

check if there's short code override

input

$short_code_id

sql

```
select c.incoming_short_code_id, g.id from carrier_shortcode_override c,short_codes sc,gateways g where c.incoming_short_code_id=? and c.incoming_short_code_id=sc.id and sc.gateway_id=g.id
```

return

$shortcode_override_id, $gateway_id

get_service_group

input

service_id

sql

```
select service_group_id from services where id=?
```

return

service_group_id

get_service_url

input service_id

sql

```
select c.sub_uri,s.wap_title,sc.short_code from services s,short_codes sc,company c where s.id=? and s.mt_short_code_id=sc.id and s.company_id=c.id
```

return $uri,$title,$sc

add_subscriber

sql

```
insert into mt_subscribers ( msisdn, active, subscription_date, keyword, short_code, mobile_carrier_id, service_id, source, sub_short_code, user_ip, affiliate_uri, reference_service_id, email) values (?,'y',now(),?,?,?,?,?,?,?,?,?,?)
```

return

$id

Sponsored by **Readable.com**
Measure your website readability!
https://readable.com

add_subscribers_tiny

input

$mt_subscriber_id, $short_uri

sql

insert into mt_subscribers_tiny_uri(mt_-subscriber_id, shortend) values(?,?)

shortend

random 6 characters string

return $shortend_uri

short_uri . $shortend

get_application_settings

input

app_name

sql

select app_m.svc_msg_type_id,ap-p_p.msg_priority_id,app.id from applic-ations app,application_msgs app_m,app-lication_priority app_p where app.name=? and app.id=app_m.app_id and app.id=app_p.app_id

return

$msg_priority_id,$msg_type_id,$app_id

note

$msg_type_id: list of ids separate by ','

set_customer_credit

input

$subscriber_id, $credit_value

sql

insert into customer_credit (mt_subscrib-er_id,credit) values (?,?)

return: $id

id of record table customer_credit

insertSubscriberLog

input

$s_id, $key_id, $billed, $kw, $short-_code, $mobile_carrier_id

sql

insert into mt_subscription_log (mt_su-bscriber_id, key_id, billed, request_date, keyword, short_code, mobile_carrier_id) values (?,?,?,now(),?,?,?)

return

$billed_id

get_gatewayid_api_name

input

short_code_id

sql

select sc.gateway_id, g.api_name, sc.premium from short_codes sc, gateways g where sc.id=? and sc.gat-eway_id=g.id

return

$gateway_id, $api_name, $premium

example

5, sybase, y

Sponsored by **Readable.com**
Measure your website readability!
https://readable.com