

Pod Commands

kubectl get nodes	Get list of all nodes
kubectl get pods --all-namespaces	Get list of all pods in all namespaces
kubectl apply -f calico.yaml	Apply a Calico Container Networking Configuration
kubectl init --apiserver-advertise-address<pvt_ip_addr> --pod-network-cidr=192.168.0.0/16	Initialise current node as Manager with Calico Container N/w soln
kubectl get pods --all-namespaces -o wide	List pods and their nodes (ip addrs)

Service Commands

Create Service	kubectl create service nodeport nginx --tcp=80:80
List services	kubectl get svc

Nodeport is the type of service endpoint being created. It allows an external client to access the service (One out of 3 types).

Administration Commands

kubectl get all	Get all resources in a namespace
kubectl get all -A	Get all resources in ALL Namespaces
kubectl config view	Show Kubectl context.

Deployment Commands

kubectl get deployments	Get deployments
-------------------------	-----------------

Kubectl Commands

kubectl config	Context and Configuration. view, get-contexts, current-context, use-context, set-cluster, set-credentials, set-context, use-context, unset
kubectl apply	Create and Update Resources. -f ./my1.yaml -f ./my2.yaml
kubectl create	Create a single instance. deployment nginx --image=nginx cronjob job



Kubecttl Commands (cont)

kubecttl explain	Get documentation, Schema Definition
	Pod
	Pod.spec.containers
kubecttl get	Viewing & Finding Resources
	services
	pods --all-namespaces
	pods -o wide
	deployment my-dep
	pod my-pod-o yaml
kubecttl describe	Obtain real-time info abt resources
	nodes my-node
	pods my-pod
kubecttl set	
kubecttl rollout	
kubecttl replace	
kubecttl expose	
kubecttl label	
kubecttl annotate	
kubecttl patch	
kubecttl edit	
kubecttl scale	
kubecttl delete	
kubecttl logs	
kubecttl run	
kubecttl attach	
kubecttl port-forward	
kubecttl exec	
kubecttl debug	
kubecttl top	
kubecttl cp	
kubecttl cordon	
kubecttl drain	
kubecttl uncordon	
kubecttl cluster-info	
kubecttl taint	



Google Cloud

Create a K8s Cluster	<code>gcloud container clusters create [CLUSTER-NAME]</code>
Authenticate Cluster to interact with it i.e Update kubeconfig	<code>gcloud container clusters get-credentials [CLUSTER-NAME]</code>
Create a deployment on created cluster	<code>kubectl create deployment [DEPL_NAME] --image=gcr.io/[PATH]/[IMG_NAME]:[TAG]</code>
Expose created deployment to external network i.e Create Service	<code>kubectl expose deployment [DEPL_NAME] --type=LoadBalancer --port [PORT]</code>
Inspect created Service	<code>kubectl get service</code>
Delete Cluster	<code>gcloud container clusters delete [CLUSTER-NAME]</code>

C

By **Nilesch** (niparkhe)
cheatography.com/niparkhe/

Not published yet.
Last updated 30th July, 2024.
Page 3 of 3.

Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish
Yours!
<https://apollopad.com>