

if command

```
if(expression) endif()
```

```
if(expression) else() endif()
```

```
if(expression) else() elseif(expression2) endif()
```

True = 1, ON, YES, TRUE, Y, or a non-zero number.

False = 0, OFF, NO, FALSE, N, IGNORE, "", or ends in the suffix '-NOTFOUND'.

```
if(NOT expression)
```

```
if(<expr1> AND <expr2>)
```

```
if(<expr1> OR <expr2>)
```

```
if(TARGET target-name) True if the given name is an existing target, built or imported.
```

```
if(EXISTS full-path-file-name) if(EXISTS full-path-directory-name)
```

```
if(IS_DIRECTORY directory-name)
```

```
if(IS_ABSOLUTE path)
```

Add Custom...

```
add_custom_command(      add_cu-
OUTPUT output(s)        stom_t-
COMMAND command arg(s)  arget(
DEPENDS depend(s)       name
WORKING_DIRECTORY dir   [ALL]
COMMENT comment) This   DEPENDS
defines a command to    depends-
generate specified OUTPUT on ... )
file(s)
```

```
add_custom_command(TARGET target
PRE_BUILD | PRE_LINK | POST_BUILD
COMMAND command arg(s) WORKIN-
G_DIRECTORY dir COMMENT comment )
```



By **p.r.thompson**
cheatography.com/p-r-thompson/

Not published yet.
Last updated 12th May, 2016.
Page 1 of 1.

Sponsored by **Readable.com**
Measure your website readability!
<https://readable.com>