

### if command

```
if(expression) endif()
```

```
if(expression) else() endif()
```

```
if(expression) else() elseif(expression2) endif()
```

True = 1, ON, YES, TRUE, Y, or a non-zero number.

False = 0, OFF, NO, FALSE, N, IGNORE, "", or ends in the suffix '-NOTFOUND'.

```
if(NOT expression)
```

```
if(<expr1> AND <expr2>)
```

```
if(<expr1> OR <expr2>)
```

```
if(TARGET target-name) True if the given name is an existing target, built or imported.
```

```
if(EXISTS full-path-file-name) if(EXISTS full-path-directory-name)
```

```
if(IS_DIRECTORY directory-name)
```

```
if(IS_ABSOLUTE path)
```

### Add Custom...

```
add_custom_command(          add_cu-  
OUTPUT output(s) COMMAND    stom_t-  
command arg(s) DEPENDS      arget(  
depend(s) WORKING_DIRE-    name  
CTORY dir COMMENT comment) [ALL]  
This defines a command to   DEPENDS  
generate specified OUTPUT   depends-  
file(s)                      on ... )
```

```
add_custom_command(TARGET target  
PRE_BUILD | PRE_LINK | POST_BUILD  
COMMAND command arg(s) WORKING_D-  
IRECTORY dir COMMENT comment )
```



By **p.r.thompson**  
[cheatography.com/p-r-  
thompson/](http://cheatography.com/p-r-thompson/)

Not published yet.  
Last updated 12th May, 2016.  
Page 1 of 1.

Sponsored by **CrosswordCheats.com**  
Learn to solve cryptic crosswords!  
<http://crosswordcheats.com>