

First line

Windows Registry Editor Version 5.00

Key format

```
[<Hive name>\<Key name>\<Subkey name>]
@=<Value type>:<Value data>
"Value name"=<Value type>:<Value data>
```

Value types

@=	(Default) value
"Value name"="String value with escape characters"	String value

Deleting Keys or Values

```
[-<Hive name>\<Key name>\<Subkey name>] Delete Key
```

@- Delete (Default) value

"Value name"=- Delete value

The '-' character in the correct place for the Key or Value will delete it

Root Keys

HKEY_LOCAL_MACHINE	HKLM	
HKEY_CURRENT_CONFIG	HKCC	Win 98 & NT only
HKEY_CLASSES_ROOT	HKCR	File associations & OLE Object Class IDs
HKEY_CURRENT_USER	HKCU	Linked to the current User's key in HKU
HKEY_USERS	HKU	User profiles
HKEY_PERFORMANCE_DATA		Win NT only but invisible
HKEY_DYN_DATA		Win 98 only

Escape characters

\ " Precede characters with a backslash '\'



By **Matthew Perryman (PezMat)**
cheatography.com/pezmat/

Not published yet.
 Last updated 27th April, 2016.
 Page 1 of 1.

Sponsored by **Readability-Score.com**
 Measure your website readability!
<https://readability-score.com>