Symfony 5 Cheat Sheet

by Marcel Berteler (pluk77) via cheatography.com/55947/cs/14851/

Entity Manager in a controller

$this->getDoctrine()->getManager();	Get default entity manager
$this->getDoctrine()->getManagerForClass(MyEntity::class)	Get entity specific manager

Repositories in a controller

```
$this->getDoctrine()->getRepository(MyEntity::class);
```

Doctrine Query

getResult($hydrationMode = self::HYDRATE_OBJECT)	Retrieve a collection
getSingleResult($hydrationMode = null)	Retrieve a single result or exception
getOneOrNullResult($hydrationMode = null)	Retrieve a result or NULL
getArrayResult()	Retrieve an array
getScalarResult()	Retrieves a flat/rectangular result set of scalar values
getSingleScalarResult()	Retrieves a single scalar value or exception
AbstractQuery::HYDRATE_OBJECT	Object graph **default**
AbstractQuery::HYDRATE_ARRAY	Array graph
AbstractQuery::HYDRATE_SCALAR	Flat rectangular result with scalars
AbstractQuery::HYDRATE_SINGLE_SCALAR	Single scalar value
AbstractQuery::HYDRATE_SIMPLEOBJECT	Very simple object **fast**
setCacheMode($cacheMode)	
Cache::MODE_GET	may read, not write
Cache::MODE_PUT	no read, write all
Cache::MODE_NORMAL	read and write

Doctrine Query (cont)

Cache::MODE_REFRESH	no read, only refresh
setCacheable($trueFalse)	Enable/disable result caching

Magic repository functions

find($id)	Returns one entity
findOneBy($criteria, $orderBy)	Returns one entity
findBy($criteria, $orderBy, $limit, $offset)	Returns collection
$criteria = ['field' => 'value']	Single field / value
$criteria = ['field' => ['value1', 'value2']]	Single where-in
$criteria = ['field1' => 'value', 'field2' => 'value2']	multiple fields / values

```
$repository = $this->getDoctrine()->getRepository(Product::class);
$product = $repository->findOneBy(['name' => 'Keyboard']);
```

Doctrine criteria - filtering collections

where($Expression)	Replaces previous statement
[and/or]**Where**($Expression)	Adds AND /OR where statement
orderBy($array)	Sets OrderBy
setFirstResult($firstResult)	Sets first result
setMaxResult($max)	Sets Maximum results

```
$userCollection = $group->getUsers();

$criteria = Criteria::create()
->where(Criteria::expr()->eq("birthday", "1982-02-17"))
->orderBy(array("username" => Criteria::ASC))
->setFirstResult(0)
->setMaxResults(20)
;
$birthdayUsers = $userCollection->matching($criteria);
```

By **Marcel Berteler** (pluk77)
cheatography.com/pluk77/

Published 18th April, 2023.
Last updated 10th May, 2023.

Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
https://apollopad.com

Cheatography

Symfony 5 Cheat Sheet

by Marcel Berteler (pluk77) via cheatography.com/55947/cs/14851/

Doctrine ExpressionBuilder and Expr

andX($arg1, $arg2, ...)	Multiple arguments AND
orX($arg1, $arg2, ...)	Multiple arguments OR
[n]**eq**($field, $value)	[Not] Equal
gte	Greater than [or equal]
lte	Less than [or equal]
isNull($field)	Is Null
[not]**in**($field, array $values)	[not] In
memberOf($field, $value)	**ExpressionBuilder only** Member of
isMemberOf($field, $value)	**Expr only** Member of
isNotNull($field)	**Expr only** Is not Null
between($field, $x, $y)	**Expr only** Between $x and $y
trim($field)	**Expr only** Trim
concat($x, $y)	**Expr only** Concat
literal($string)	**Expr only** Literal
lower($field)	**Expr only** Lower case
upper($field)	**Expr only** Upper case
count($field)	**Expr only** count

```
# Doctrine Expr #
Criteria::expr()->orX(
Criteria::expr()->eq('id', $facilityId),
Criteria::expr()->eq('active', TRUE)
);

# Doctrine ExpressionBuilder #
$qb = $this->createQueryBuilder('f');

$qb->where($qb->expr()->eq('id', '?arg1'))
->setParameter('arg1', $facilityId);

$qb->select($qb->expr()->substring('o.orderNumber', 4, 3));

$qb->select($qb->expr()->concat('p1.surname', $qb->expr()->literal(','), 'p1.firstName');
```

Doctrine Query Builder

setParameter($parameter, $value)
addCriteria(Criteria $criteria)
[get/set]**MaxResults**($maxResults)
[get/set]**FirstResult**($firstResult)
getQuery()

Doctrine Query Builder (cont)

add($dqlPartName, $dqlPart, $append = false)
$dqlPartName: select, from, join, set, where, groupBy, having, orderBy
Wrappers for add():
[add]**select**($select= null)
delete($delete = null, $alias = null)
update($update = null, $alias = null)
set($key, $value)
from($from, $alias, $indexBy = null)
[inner/left]**join**($join, $alias, $conditionType = null, $condition = null, $indexBy = null)
[and/or]**where**($where)
[add]**groupBy**($groupBy)
[and/or]**having**($having)
[add]**orderBy**($field, $order = null)

Doctrine raw SQL

$Connection= $EntityManager->**getConnection**(): Connection;	Get connection
$Statement = $Connection->**prepare**(string $sql): Statement;	Prepare statement from string
$Statement->**bindValue**(string|int $param, $value, $type = null): bool	Bind a value to a corresponding name
$Statement->**execute**(?array $params = null): bool	Execute the statement
$Statement->**fetchAll**(int $fetchStyle = PDO::FETCH_BOTH): array	Fetch all results
$Statement->**fetchOne**(int $fetchStyle = PDO::FETCH_BOTH): array	Fetch single result
$Statement->**rowCount**(): int	Return the number of rows

Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
https://apollopad.com

Doctrine raw SQL (cont)

$Statement->**free**(): void	Free stored result memory

```
$connection = $entityManager->getConnection();

$sql = 'SELECT * FROM events WHERE start_date >= :startdate';

$statement = $conn->prepare($sql);
$statement->bindValue('startdate', $startDate->format('Y-m-d H:i:s'));
$statement->execute();

return $statement->fetchAll();
```

Authorization

IS_AUTHENTICATED_FULLY	User has successfully authenticated, not via 'remember me cookie'
IS_AUTHENTICATED_REMEMBERED	All logged in users
IS_REMEMBERED	Only users authenticated using the remember me functionality
IS_IMPERSONATOR	When the current user is impersonating another user in this session

All roles you assign to a user must begin with the ROLE_ prefix in order for the default symfony RoleVoter to vote. Other prefixes require a custom voter.

Authorization in a controller

```
# Example of using wrapper #
public function hello($name)
{
// The second parameter is used to specify on what object the role is tested.
$this->denyAccessUnlessGranted('ROLE_ADMIN', null, 'Unable to access this page!');
// ...
}
# Example of using AuthorizationChecker
use Symfony\Component\Security\Core\Authorization\AuthorizationCheckerInterface
use Symfony\Component\Security\Core\Exception\AccessDeniedException;
public function hello($name, AuthorizationCheckerInterface $authChecker)
{
```

Authorization in a controller (cont)

```
if (false === $authChecker->isGranted('ROLE_ADMIN')) {
throw new AccessDeniedException('Unable to access this page!');
}
// ...
}
# Example of using annotation #
use Sensio\Bundle\FrameworkExtraBundle\Configuration\Security;
/**
* @Security("has_role('ROLE_ADMIN')")
*/
public function hello($name)
{
// ...
}
```

Persisting Entities

```
// get the entity manager that manages this entity
$em = $this->getDoctrine()->
getManagerForClass(MyEntity::class);
// create a new entity
$entity = new MyEntity();
// populate / alter properties
$entity->setName('Default Entity');
// tell Doctrine you want to (eventually) save
$em->persist($entity);
// actually executes the queries
$em->flush();
```

Authorization via security.yaml

```
# config/packages/security.yaml
security:
access_control:
# public access only for /
```


Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
https://apollopad.com

Authorization via security.yaml (cont)

```
- { path: ^/$, roles: PUBLIC_ACCESS }
# public access to login page /login
- { path: ^/login, roles: PUBLIC_ACCESS }
# or require ROLE_ADMIN or ROLE_USER_ADMIN for
/admin/users*
- { path: '^/admin/users', roles: [ROLE_USER_ADMIN, ROLE_A-
DMIN] }
# require ROLE_ADMIN for /admin*
- { path: ^/admin, roles: ROLE_ADMIN }
# authenticated users only to the rest /*
- { path: ^/, roles: IS_AUTHENTICATED_FULLY
```

No limit on amount of URL patterns. Each is a regular expression. First match will be used.

Prepend the path with ^ to ensure only URLs beginning with the pattern are matched.

Authorization in template

```
{% if is_granted('ROLE_ADMIN') %}
<a href="...">Delete</a>
{% endif %}
```

Create a new form in a controller

```
# Create a new form with a default name #
$form = $this->createFormBuilder($data)
->add('dueDate', null, array(
'widget' => 'single_text'))
->add('save', SubmitType::class)
->getForm();
# Create a form with a non-default name #
$form = $this->container->get('form.factory')
->createNamedBuilder(
'form1', FormType::class, $data)
->add('dueDate', null, array(
'widget' => 'single_text'))
->add('save', SubmitType::class)
->getForm();
```

Create a form from a class in a controller

```
# Create a form from a form class with a default name #
$form = $this->createForm(TaskForm::class, $data, array(
'action' => $this->generateUrl('target_route'),
'method' => 'GET',
));
# Create a form from a form class with a non-default name #
$form = $this->container->get('form.factory')
->createNamed('form1', TaskForm::class, $data, array(
'action' => $this->generateUrl('target_route'),
'method' => 'GET',
));
```

Form Options

'action' => ''	Where to send the form's data on submission (usually a URI)
'allow_extra_fields' => false	Allow additional fields to be submitted
'error_mapping' => array('matchingCityAndZipCode' => 'city')	Modify the target of a validation error
'extra_fields_message' => 'This form should not contain extra fields.'	Validation error message if additional fields are submitted
'inherit_data' => false	Inhered data from parent form or not
'method' => 'POST'	HTTP method used to submit the form
'post_max_size_message' => 'The uploaded file was too large.'	Validation message for size of post form data

Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
https://apollopad.com

Form Options (cont)

'validation_groups' => false	Disable the Validation of Submitted Data

```
public function configureOptions(OptionsResolver $resolver) {
$resolver->setDefaults(array(
# Options go here #
));
}
```

Log Levels / Console Verbosity (OutputInterface)

emerge-ncy()	System is unusable.		
alert()	Action must be taken immediately.		
critical()	Critical conditions.		
error()	Runtime errors that do not require immediate action but should typically be logged and monitored.	VERBOS-ITY_QUIET (-1)	-q / stderr
warning()	Exceptional occurrences that are not errors.	VERBOS-ITY-_NORMAL (0)	(non) / stdout
notice()	Normal but significant events.	VERBOS-ITY_VE-RBOSE (1)	-v
info()	Interesting events.	VERBOS-ITY_VE-RY_-VERBOSE (2)	-vv
debug()	Detailed debug information.	VERBOS-ITY-_DEBUG (3)	-vvv

```
use Psr\Log\LoggerInterface;

public function index(LoggerInterface $logger) {
$logger->info('I just got the logger');
}
```

Console

bin\console	List available commands and show the Symfony version
server:run	Run the built-in web server
assets:install --symlink	Install bundle assets as a symlink or hardcopy
debug:autowire	Lists classes/interfaces you can use for autowiring
debug:config	Dumps the current configuration for an extension
debug:container	Displays current services for an application
debug:form	Lists classes/interfaces you can use for autowiring
debug:route	Displays current routes for an application

```
Usage:
php bin\console command [options] [arguments]

Options:
-h, --help Display this help message
-q, --quiet Do not output any message
-n, --no-interaction Do not ask any interactive question
-e, --env=ENV The environment name [default: "dev"]
--no-debug Switches off debug mode
-v|vv|vvv, --verbose Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug
```

Basic form

```
class TaskForm extends AbstractType
{
public function buildForm(
FormBuilderInterface $builder,
array $options)
{
$builder
->add('dueDate', DateType::class, array(
'widget' => 'single_text',
```


Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
https://apollopad.com

Basic form (cont)

```
'label' => 'Due Date',
'required' => false,
'attr' => array('maxlength' => 10),
'constraints' => array(new Length(
array('max' => 10)))
))
->add('save', SubmitType::class);
}
public function configureOptions(
OptionsResolver $resolver)
{
$resolver->setDefaults(array(
'method' => 'GET',
));
}
}
```

TwigBridge - Forms

{{ **form**(view, variables) }}	Render whole form
{{ **form_start**(view, variables) }}	Render start tag
{{ **form_errors**(view) }}	Render global errors
{{ **form_row**(view, variables) }}	Render all the fields
{{ **form_rest**(view, variables) }}	Render all other fields
{{ **form_end**(view, variables) }}	Render end tag + all other fields
{{ **form_row**(view.field) }}	Render field label, error and widget
{{ **form_label**(view.field, label, variables) }}	Render field label

TwigBridge - Forms (cont)

{{ **form_errors**(view.field) }}	Render field error
{{ **form_widget**(view.field, variables) }}	Render field widget

```
{# render a label, but display 'Your Name' and add a "foo" class to it #}
{{ form_label(form.name, 'Your Name', {'label_attr': {'class': 'foo'}}) }}

{# render a widget, but add a "foo" class to it #}
{{ form_widget(form.name, {'attr': {'class': 'foo'}}) }}

{# render a field row, but display a label with text "foo" #}
{{ form_row(form.name, {'label': 'foo'}) }}
```

Response from a controller

render($view, $parameters, $response = null)	Render the template and return a Response
json($data, $status = 200, $headers = array(), $context = array())	Encode data and return a Json response
file($file, $fileName = null, $disposition = ResponseHeaderBag::DISPOSITION_ATTACHMENT)	Return a file response
redirectToRoute($route, $parameters = array(), $status = 302)	Redirect to route
redirect($url, $status = 302)	Redirect to external URL
forward($controller, $path = array(), $query = array())	Forwards the request to another controller

```
return $this->render('admin/post/show.html.twig', [
    'post' => $post,
    'delete_form' => $deleteForm->createView(),
]);

return $this->json($data);
```


Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
https://apollopad.com