

CREATE ".git" DIRECTORY

```
git init
```

CONNECT THIS DIRECTORY AND THAT REPOSITORY

```
cd THIS_DIRECTORY
git remote add origin git@bitbucket.org:TEAM_NAME/THAT_REPO_NAME.git
```

ADD ALL CHANGE

```
git add -A
```

PUSH COMMIT ON THAT REPOSITORY

```
cd THIS_DIRECTORY_THAT_HAVE_.GIT
git push -u origin master
```

ADD .gitignore FOR MY CMS

go to gitignore.io

search my cms and copy syntax

```
cd TO_ROOT_OF_THE_GIT_DIRECTORY
```

```
nano .gitignore
```

paste of syntax & save file

CREATE "README.md" FILE

```
nano README.md
```

GET CLONE ON THIS DIRECTORY FROM THAT REPOSITORY

```
git clone -v --progress
git@bitbucket.org:TEAM_NAME/THAT_REPO_NAME.git
/THIS_DIRECTORY_ADDRESS
```

COMMIT ALL CHANGE WITH A COMMAND

```
git commit -m "TYPE_YOUR_COMMAND"
```

CREATE PRIVATE KEY ON MY SYSTEM

```
CREATE ssh-keygen -t rsa
```

```
SHOW CONTENT ON MY PRIVATE KEY cat ~/.ssh/id_rsa.pub
```



By **Alireza Pourabedin**
(pourabedin.alireza)

Published 7th February, 2015.

Last updated 13th May, 2016.

Page 1 of 1.

Sponsored by **Readable.com**

Measure your website readability!

<https://readable.com>