

Sorting algorithms and Methods

Sorting algorithms	Methods
Bubble sort	Exchanging
Heapsort	Selection
Insertion sort	Insertion
Introsort	Partitioning & Selection
Merge sort	Merging
Patience sorting	Insertion & Selection
Quicksort	Partitioning
Selection sort	Selection
Timsort	Insertion & Merging
Unshuffle sort	Distribution and Merge

Best and Worst Case

Algorithms	Best Case	Worst Case
Bogosort	n	∞
Bubble sort	n	n^2
Bucket sort (uniform keys)	-	n^2k
Heap sort	$n \log n$	$n \log n$
Insertion sort	n	n^2
Merge sort	$n \log n$	$n \log n$
Quick sort	$n \log n$	n^2
Selection sort	n^2	n^2
Shell sort	$n \log n$	$n^{4/3}$
Spreadsort	n	$n(k/s+d)$
Timsort	n	$n \log n$
Unshuffle sort	n	kn

Insertion sort

```
function insertionSortR(array A, int n)
    if n>0
        insertionSortR(A,n-1)
        x ← A[n]
        j ← n-1
        while j >= 0 and A[j] > x
            A[j+1] ← A[j]
            j ← j-1
        end while
        A[j+1] ← x
    end if
end function
```

Merge sort

```
function merge_sort(list m)
    // Base case. A list of zero or one elements is sorted, by definition.
    if length of m ≤ 1 then
        return m
    // Recursive case. First, divide the list into equal-sized sublists
    // consisting of the first half and second half of the list.
    // This assumes lists start at index 0.
    var left := empty list
    var right := empty list
    for each x with index i in m do
        if i < (length of m)/2 then
            add x to left
        else
            add x to right
    // Recursively sort both sublists.
    left := merge_sort(left)
    right := merge_sort(right)
    // Then merge the now-sorted sublists.
    return merge(left, right)
```

Bogosort

```
while not isInOrder(deck):
    shuffle(deck)
```

Bucket sort

```
function bucketSort(array, n) is
    buckets ← new array of n empty lists
    for i = 0 to (length(array)-1) do
        insert array[i] into buckets[middle(-array[i], k)]
    for i = 0 to n - 1 do
        nextSort(bucket s[i]);
    return the concatenation of bucket s[0],
    ...., bucket s[n-1]
```

Resources

https://en.wikipedia.org/wiki/Sorting_algorithm#Comparison_of_algorithms

<http://bigocheatsheet.com>



By Priyal kumar (pryl)
cheatography.com/pryl/
priyal-kumar.blogspot.com/

Published 27th August, 2018.
 Last updated 27th August, 2018.
 Page 1 of 2.

Sponsored by [ApolloPad.com](https://apollopad.com)
 Everyone has a novel in them. Finish Yours!
<https://apollopad.com>

Cheatography

Sorting algorithms Cheat Sheet by Priyal kumar (pryl) via cheatography.com/66402/cs/16808/

Sorting algorithm complexities

Algorithms	Average Case	Memory complexity
Bitonic sorter	$\log^2 n$	$n \log^2 n$
Bogosort	$n \times n!$	1
Bubble sort	n^2	1
Bucket sort (uniform keys)	$n+k$	nk
Burstsort	$n(k/d)$	$n(k/d)$
Counting sort	$n+r$	$n+r$
Heap sort	$n \log n$	1
Insertion sort	n^2	1
Introsort	$n \log n$	$\log n$
LSD Radix Sort	$n(k/d)$	$n+2^d$
Merge sort	$n \log n$	n
MSD Radix Sort (in-place)	$n(k/d)$	2^d
Patience sort	-	n
Pigeonhole sort	$n+2^k$	2^k
Quicksort	$n \log n$	$\log n$
Selection sort	n^2	1
Shell sort	Depends on gap sequence	1
Spaghetti sort	n	n^2
Spreadsort	$n(k/d)$	$(k/d)2^d$
Stooge sort	$n^{(\log 3/\log 1.5)}$	n
Timsort	$n \log n$	n

Bubble sort (cont)

```
> end procedure
```

Quicksort

```
algorithm quicksort(A, lo, hi) is
    if lo < hi then
        p := partition(A, lo, hi)
        quicksort(A, lo, p - 1)
        quicksort(A, p + 1, hi)

algorithm partition(A, lo, hi) is
    pivot := A[hi]
    i := lo
    for j := lo to hi - 1 do
        if A[j] < pivot then
            swap A[i] with A[j]
            i := i + 1
    swap A[i] with A[hi]
    return i
```

Selection sort

```
procedure selection sort
    list : array of items
    n : size of list
    for i = 1 to n - 1
        set current element as minimum/
        min = i

        check the element to be minimum /
        for j = i+1 to n
            if list[j] < list[min] then
                min = j;
            end if
        end for

        swap the minimum element with the current
        element/
        if indexMin != i then
            swap list[min] and list[i]
        end if
    end for

end procedure
```

Bubble sort

```
procedure bubbleSort( A : list of sortable items )
    n = length(A)
    repeat
        swapped = false
        for i = 1 to n-1 inclusive do
            if A[i-1] > A[i] then
                swap(A[i-1],
A[i])
                swapped = true
            end if
        end for
        n = n - 1
    until not swapped
```

C

By Priyal kumar (pryl)
cheatography.com/pryl/
priyal-kumar.blogspot.com/

Published 27th August, 2018.
Last updated 27th August, 2018.
Page 2 of 2.

Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish
Yours!
<https://apollopad.com>