

CSS SELECTOR ↗

SELECTOR	MEANING	EXAMPLE
UNIVERSAL SELECTOR	Applies to all elements in document	*{} Targets all elements on page
TYPE SELECTOR	Matches elements names	h1 h2 {} Targets<h1> <h2> elements on page
CLASS SELECTOR	Matches an element whose class attribute has value that matches the one specified after full stop	.class{} Targets any element whose class attribute has a value of class
ID SELECTOR	Matches an element whose id attribute has value that matches the one specified after hash sign	#intro {} Targets any element whose id attribute has a value of intro
CHILD SELECTOR	Matches an element that is a direct child of another	li > a {} Targets any <a> elements that are children of any element
DESCENDANT SELECTOR	Matches an element that is a descendant of another specified element	p a {} Targets any <a> elements that sit inside any <p> element
ADJACENT SIBLING SELECTOR	Matches an element that is next sibling of another	h1 + p {} Targets first <p> element after any <h1> element
GENERAL SIBLING SELECTOR	Matches an element that is a sibling of another, although it does not have to be the directly preceding element	h1 ~ p {} if you had two elements that are siblings of an element, this rule would apply to both

rahilkasimi@gmail.com



By **Rahil (rahilkasimi)**
cheatography.com/rahilkasimi/

Published 11th May, 2022.
Last updated 11th May, 2022.
Page 2 of 2.

Sponsored by **Readable.com**
Measure your website readability!
<https://readable.com>

