

Introduction

Overview of SciTECO as an editor as of v2.0.0. A full language description can be read in [sciteco\(7\)](#).

Legend

$\$$ String delimiter (escape key)

$\$\$$ Terminate command line

n Some number (implied 1). Usually you can write $-$ instead of -1 .

text Arbitrary *text*

q A named storage area called a Q-register. Use any single character to name the register. There are also two letter names initiated by # and long names in [. . .] braces.

$\wedge X$ Ctrl+ X , but can also be types with a caret \wedge .

LF Line Feed, ie. Enter/Return key

For instance: $-C = -1C = R$

$Qa = Q[A]$, $Q\#ab = Q[AB]$

$Ctrl+I = \wedge I = \text{Tab key}$, $Ctrl+J = \wedge J = LF$

Exiting

EX\$	Exit, but only if no buffer is "dirty" (unsaved).
-EX\$	Exit even if buffer is "dirty", ie. discarding all unsaved changes.
:EX\$	Exit, saving all "dirty" buffers.

File Commands

EB <i>filename</i> \$	Edit buffer or open new file. Files, that did not exist on disk, will not be created until you save them.
EB\$	Edit the unnamed buffer.
0EB	Show buffer ring/list. You can specify a filename afterwards to open a file.
<i>n</i> EB\$	Select <i>n</i> -th buffer in ring.
EW\$	Write (save) current buffer under its current name. Does not work on the unnamed buffer.
EW <i>filename</i> \$	Save current buffer under new name (Save As).
EF	Finish (close) current buffer.
-EF	Finish (close) current buffer, discarding all unsaved changes.
FG <i>path</i> \$	Go to folder <i>path</i> , ie. change working directory.

Tip: You can use the Tab-key for autocompleting filenames and paths.

Copy & Paste

X q	Copy from current position until beginning of next line into Q-Register q .
n X q	Copy next n lines into Q-Register q .
n :X q	Append next n lines into Q-Register q .
n X q n K	Cut next n lines into Q-Register q .
HX q	Copy entire buffer in to Q-Register q .
G q	Get (paste) Q-Register q at current position.
I...^EQ q ...	Paste Q-Register q while inserting text.
E% q FILE\$	Save Q-Register q into <i>FILE</i> .
EQQ\$	Edit Q-Register q as a text buffer.
EQQFILE\$	Read <i>FILE</i> into Q-Register q .

Text Insertion

I <i>text</i> \$	Insert <i>text</i> into buffer.
^I <i>text</i> \$	Insert <i>text</i> with leading tab/indentation. Can be typed with the Tab-key!

Cursor Movement

C	Move one character forward.
n C	Move n characters forward.
R	Move one character backwards (<i>reverse</i>).
n R	Move n characters backwards.
W	Move to the beginning of next word.
L	Move to the beginning of next line.

Cursor Movement (cont)

n L	Move forward n lines.
0L	Go to the beginning of the current line.
n B	Move backwards n lines.
J n L	Go to line $n+1$.
J	Jump to beginning of buffer.
n J	Jump to character n .
ZJ	Jump to end of buffer.

Tip: Enable the `fnkeys.tes` module in `~/ .tec o-ini` to move around with cursor keys!

Text Deletion

D	Delete next character.
n D	Delete next n characters.
V	Delete next word.
n V	Delete next n words.
n Y	Delete previous n words.
FKLF\$	Delete remainder of line.
K	Kill (delete) from current position to beginning of next line.
0K	Kill (delete) to the beginning of line.
0KK	Delete entire line.
n K	Kill (delete) next n lines.
HK	Kill (delete) the whole buffer.



By rhaberkorn

cheatography.com/rhaberkorn/

Not published yet.

Last updated 22nd June, 2023.

Page 2 of 2.

Sponsored by CrosswordCheats.com

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>