

Text Effects	
strong	bold
<i>_emphasis_</i>	<i>italic</i>
??citation??	Citation
-deleted-	strikethrough
+inserted+	underlined
^superscript^	superscript
~subscript~	subscript
{{monospace}}	monosp ace /code
bq. Text	Block quote, like Cheato- graphy's Answer block
{quote} quotable paragraph {quote}	Block quote a multiline paragraph
{color:red} text {color}	Text color

Links	
[#anchor]	Internal link to an
[^attachment.ext]	anchor or attachment
[http://exam- ple.com]	External link
[Alias][http://...]	External link with alias
[mailto:foobar@- example.com]	Email link, with icon
[file:///c:/tmp/fo- o.txt]	Download link to a file
{anchor:anch- orname}	Creates an anchor
[~username]	Link to user profile page

Text Breaks	
(empty line)	Produces a new paragraph
\\	Creates a line break
----	Horizontal ruler
---	Long dash symbol
--	Dash symbol

Attachments	
Some attachments of a specific type can be embedded into a wiki renderable field from attached files, taking in a comma-separated list of properties:	
!quick tim e.mov!	
!space Key :pa geT itl e^a tta chm -	
ent.mov!	
!quick tim e.m ov wid th= 300 ,he -	
igh t=40!	
!media.wm v i d=m edia!	

Tables	
heading 1 heading 2 heading 3	
col A1 col A2 col A3	
col B1 col B2 col B3	
Makes a table. Use double bars for a table heading row.	

Lists	
* some	A bulleted list (must be in first column)
* bullet	
** indented	
** bullets	
* points	
# a	A numbered list (must be in first column).
# numbered	
# list	
- different	List items (with -), several lines create a single list
- bullet	
- types	
Use more (**, ***, ##, ###) for deeper indentations. Bulleted and numbered lists can be mixed (#*, *#).	

Headings	
h1	Biggest heading
h2	Bigger heading
h3	Big heading
h4	Normal heading
h5	Small heading
h6	Smallest heading

To create a header, place "hn. " at the start of the line (where n can be a number from 1-6).

Images	
!http://example.com/img.gif!	
!attached-image.gif!	
Inserts an image into the page.	
!img.j pg thu mbnail!	
Insert a thumbnail of the image into the page.	
!img.g if ali gn= right, vspace =4!	
For any image, you can also specify attributes of the image tag as a comma separated list of name=value pairs like so.	

Misc. (Icons/emoticons)			
\x	Escape a character		
:)	😊	:(😞☐
:P	😄	:D	😁
:)	😊	(y)	👍
(n)	🗨	(i)	📍 (blue)
(/)	✅ (green)	(x)	❌ (red)
(!)	⚠ (yellow)	(+)	⊕ (green)
(-)	🚫 (red)	(?)	❓ (blue)
(on)	💡 (lit)	(off)	💡 (off)
(*)	★ (yellow)	(*r)	★ (red)
(*g)	★ (green)	(*b)	★ (blue)
(*y)	★ (yellow)		
(flag)	🚩 (red)	(flagoff)	🚩



Advanced Formatting

```
{noformat}
preformatted piece of text
so *no* further __forma tting__ is done her
e
{noformat}
```

Preformatted text block with no syntax highlighting.

```
{code:title=Bar.java}
public String getFoo() {
    return foo;
}
{code}
```

Makes a preformatted block of code with syntax highlighting. Languages: Java (default), JavaScript, ActionScript, XML, SQL.

```
{panel}
Some text
{panel}
```

Embraces a block of text within a fully customizable panel.

```
{panel :ti tle=My Title|borderStyle=dashed}
a block of text surrounded with a *panel*
{panel}
```

Panel with optional parameters.

The optional parameters you can define, for `panel` and `code`, are the following ones:
title, borderStyle, borderColor, borderWidth, bgColor, titleBGColor



By **rhorber**
cheatography.com/rhorber/

Published 1st March, 2018.
Last updated 1st March, 2018.
Page 2 of 2.

Sponsored by **Readable.com**
Measure your website readability!
<https://readable.com>