JIRA Text Formatting Notation Cheat Sheet

by rhorber via cheatography.com/45342/cs/13350/

Text Effects

strong	**bold**
emphasis	*italic*
??citation??	Citation
-deleted-	~~strikethrough~~
+inserted+	underlined
^superscript^	superscript
subscript	subscript
{{monospace}}	`monosp ace /code`
bq. Text	Block quote, like Cheatography's Answer block
{quote} quotable paragraph {quote}	Block quote a multiline paragraph
{color:red} text {color}	Text color

Links

[#anchor] [^attachment.ext]	Internal link to an anchor or attachment
[http://example.com]	External link
[Alias|http://...]	External link with alias
[mailto:foobar@example.com]	Email link, with icon
[file:///c:/tmp/foo.txt]	Download link to a file
{anchor:anchorname}	Creates an anchor
[~username]	Link to user profile page

Text Breaks

(empty line)	Produces a new paragraph
\\	Creates a line break
----	Horizontal ruler
---	Long dash symbol
--	Dash symbol

Attachments

Some attachments of a specific type can be embedded into a wiki renderable field from attached files, taking in a comma-separated list of properties:

```
!quick tim e.mov!
!space Key :pa geT itl e^a tta chm -
ent.mov!
!quick tim e.m ov| wid th= 300 ,he -
igh t=40!
!media.wm v|i d=m edia!
```

Tables

```
||heading 1||heading 2||heading
3||
|col A1|col A2|col A3|
|col B1|col B2|col B3|
```

Makes a table. Use double bars for a table heading row.

Lists

* some * bullet ** indented ** bullets * points	A bulleted list (must be in first column)
# a # numbered # list	A numbered list (must be in first column).
- different - bullet - types	List items (with -), several lines create a single list

Use more (**, ***; ##, ###) for deeper indentations. Bulleted and numbered lists can be mixed (#*, *#).

Headings

h1	Biggest heading
h2	Bigger heading
h3	Big heading
h4	Normal heading
h5	Small heading
h6	Smallest heading

To create a header, place "hn. " at the start of the line (where n can be a number from 1-6).

Images

```
!http://example.com/img.gif!
!attached-image.gif!
```

> Inserts an image into the page.

```
!img.j pg| thu mbnail!
```

> Insert a thumbnail of the image into the page.

```
!img.g if| ali gn= right, vspace
=4!
```

> For any image, you can also specify attributes of the image tag as a comma separated list of name=value pairs like so.

Misc. (Icons/emoticons)

\x	Escape a character		
:)	😊	:(	☹
:P	😛	:D	😀
;)	😉	(y)	👍
(n)	👎	(i)	ℹ (blue)
(/)	✔ (green)	(x)	✖ (red)
(!)	⚠ (yellow)	(+)	⊕ (green)
(-)	⊖ (red)	(?)	? (blue)
(on)	💡 (lit)	(off)	💡 (off)
(*)	★ (yellow)	(*r)	★ (red)
(*g)	★ (green)	(*b)	★ (blue)
(*y)	★ (yellow)		
(flag)	⚑ (red)	(flagoff)	⚐

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
http://crosswordcheats.com

Advanced Formatting

```
{noformat}
preformatted piece of text
so *no* further _forma tting_ is done her
e
{noformat}
```

> Preformatted text block with no syntax highlighting.

```
{code:title=Bar.java}
public String getFoo() {
  return foo;
}
{code}
```

> Makes a preformatted block of code with syntax highlighting. Languages: Java (default), JavaScript, ActionScript, XML, SQL.

```
{panel}
Some text
{panel}
```

> Embraces a block of text within a fully customizable panel.

```
{panel :ti tle=My Title|borderStyle=dashe
d}
a block of text surrounded with a *panel*
{panel}
```

> Panel with optional parameters.

The optional parameters you can define, for `panel` and `code`, are the following ones: title, borderStyle, borderColor, borderWidth, bgColor, titleBGColor

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
http://crosswordcheats.com