

Global Config

```
[alias]
    co = switch
    hist = log --pretty=format:'%C(yellow) [%a d]% C(reset) %C(green) [%h ]%C (reset)
| %C(red)%s %C(bold red){%an}%C(reset) %C(blue)% d%C (reset)' --graph --date=short
    fixup = "!git log -n 50 --pretty=format:'%h %s' --no-merges | fzf | cut -c -7 | xargs
-o git commit --fixup"

[core]
    editor = vim
    excludesfile = ~/.gitignore_global

[rebase]
    autosquash = true

[diff "ansiblereview"]
    textconv = ansiblereview

[commit]
    gpgsign = true

[pgp]
    program = /usr/bin/gpg

[credential "https://github.com"]
    helper =
    helper = !/usr/bin/gh auth git-credential

[credential "https://github.com"]
    helper =
    helper = !/usr/bin/gh auth git-credential
```

Rebase

Rebase with main	git rebase -i origin/main
continue rebase	git rebase --continue
Skip empty commit	git cherry-pick --skip
p, pick	use commit
r, reword	edit commit message
e, edit	amend commit
s, squash	meld into previous commit
f, fixup	like squash, but discard this commit message
x, exec	run command
b, break	stop here
d, drop	remove commit
l, label <label>	label current HEAD with a name
t, reset <label>	reset HEAD to a label
m, merge -c <commit>	create a merge commit using reworded commit

Patching

Stash	git stash -p
Add file	git add -p <file>
y	stage this hunk
n	do not stage this hunk
q	quite; do not stage this nor any remaining
a	stage this hunk and all later
d	do not stage this hunk or any later
g	select a hunk to go to
/	search for hunk matching regex
j	leave undecided; see next undecided
J	leave undecided; see next hunk
k	leave undecided; see previous undecided
K	leave undecided; see previous hunk
s	split hunk
e	manually edit hunk

Patching (cont)

? print help



By **Rihoj**
cheatography.com/rihoj/

Not published yet.
Last updated 5th March, 2023.
Page 2 of 2.

Sponsored by **Readable.com**
Measure your website readability!
<https://readable.com>