

HTTP/1.1 protocol Cheat Sheet

by SandRock via cheatography.com/78567/cs/19155/

Request and Response Messages

The HTTP protocol consist into a request message, sent from a client to a web server, and a response message, sent from the server to the originating client.

Request message general format:

HTTP Request Line HTTP Request Headers (empty line)

HTTP Request Body

Response message general format:

HTTP Response Line
HTTP Response Headers
(empty line)
HTTP Response Body

HTTP Request Line

Format: "METHOD PATH PROTOCOL"

METHOD: GET, HEAD, POST, PUT, DELETE, TRACE, OPTIONS, CONNECT, PATCH

PATH: the path of the resource PROTOCOL: HTTP/1.1

Example: GET /image s/l ogo.png HT TP/1.1

HTTP Request Headers

"NAME: VALUE"*

NAME: [A-Za- z0- 9] [A-Z a-z 0-9

-]+

VALUE: US-ASCII octets

HTTP Request Headers (cont)

Headers are extra information for the request. There are many standard headers and you can create your own.

See Common HTTP Request Headers

Example set of headers:

Host: en.wik ipe dia.org
User-A gent: Mozill a/5.0 Firefo x/64.0
Accept: text/h tml ,ap pli cat i on /xh tml +xm l,a ppl ica tio n /x ml; q=0.9,/;q=0.8
Accept -La nguage: en-GB, en- US; q=0.8, en; q=0.6, fr- FR; q=0.4, fr; q=0.2

Accept -En coding: gzip, deflate , br

Connec tion: keep-alive Cookie: Auth=8 QXA 5fS QeZ AEK Z VG 6iR jMW vQ8 KtQKAaj

HTTP Request Body

If the HTTP method used is POST or PUT, the request may be followed by a body. It can be a file or a specific form of data.

The Conten t-Type header must be filled with a MIME type to indicate the type of content.

The body is separated from the header by two line feeds (\n).

HTTP Response Line

Format: PROTOCOL STATUS REASON

PROTOCOL: HTTP/1.1

STATUS: Any HTTP *Status Code* REASON: A reason message

Published 19th March, 2019. Last updated 19th March, 2019.

Page 1 of 3.

HTTP Response Line (cont)

The reason message is usually the label associated to the status code. Some APIs may use this text field to specify an error message.

Examples:

HTTP/1.1 200 OK HTTP/1.1 404 Not Found

HTTP Response Headers

"NAME: VALUE"*

NAME: [A-Za- z0- 9] [A-Z a-z 0-9 -]+

VALUE: US-ASCII octets

Headers are extra information for the response. There are many standard headers and you can create your own.
See Common HTTP Response Headers

HTTP Response Body

The is usually a response body after the response headers. It can be a file or a specific form of data.

The Content-Type header must be filled with a MIME type to indicate the type of content.

The body is separated from the headers by two line feeds (\n).

HTTP Request Methods

GET: used to retrieve a resource. Has no request body.

POST: used to submit a new resource (path) or send data. Usually has a body.



By **SandRock** cheatography.com/sandrock/

Sponsored by Readable.com Measure your website readability! https://readable.com



HTTP/1.1 protocol Cheat Sheet

by SandRock via cheatography.com/78567/cs/19155/

HTTP Request Methods (cont)

HEAD: used to preview the result of a GEToperation. Has no request body and no respond body.

PUT: used to submit an update to an existing resource

DELETE: used to delete the specified

TRACE: echoes the received request for

tracing purposes

OPTIONS: verify the server supports a specified request (see Preflight requests)

CONNECT: used by HTTPS

PATCH: allows partial modification of a

resource

Common HTTP Request Headers

Accept	List of MIME types supported
Accept-La- nguage	List of languages read by the user
Content-L- ength	Length in bytes of the request body
Content- Type	MIME type of the request body
Cookie	List of cookies stored by the client
Host	Host name of the website
User-Agent	Identification string for the web browser

There are many more available. You can create your own headers.

> By SandRock cheatography.com/sandrock/

HTTP Status Codes	
1xx	Informational
100	Continue
2xx	Successful
200	OK
201	Created
202	Accepted
204	No Content
<i>3xx</i>	Redirection
301	Moved permanently
302	Found
304	Not Modified
308	Permanent Redirect
4xx	Client Error
400	Bad Request
401	Unauthorized
403	Forbidden
404	Not Found
405	Method Not Allowed
<i>5xx</i>	Server Error
500	Internal Server Error
502	Bad Gateway
503	Service Unavailable
504	Gateway Timeout
There are many other codes; these are the most used. You should not create your own	

codes.

Common HTTP Response Headers

Cache- Control: Indicates client caching conditions

Conten t-L ength: Length of the

response body in bytes

Conten t-Type: MIME type of the

response body

Expires: Client is allowed to keep the

resouce in cache

Location: Redirection URL

Server: name of the server software

Set-Cookie: new cookies that should be

stored client-side

There are many more available. You can create your own headers.

Content size & streaming

When a message body is exchanged, the receiver must be able to determine when the message is complete (or how many bytes should be received to consider the body complete).

The main operating way is to use the Cont

en t-L ength header with the size (in bytes) of the body that is to come. When a streaming method is desired, an alternative way is to use the Transf er-Enc oding: chunked header and to follow the Chunked transfer encoding protocol.



Published 19th March, 2019. Last updated 19th March, 2019. Page 2 of 3.

Sponsored by Readable.com Measure your website readability! https://readable.com



HTTP/1.1 protocol Cheat Sheet

by SandRock via cheatography.com/78567/cs/19155/

Notes

All specifications in this document have been simplified from the official HTTP standard. Always refer to the RFCs if necessary.

RFC-7230: Hypertext Transfer Protocol (HTTP/1.1): Message Syntax and Routing

Protocol versions

HTTP/0.9 and HTTP/1.0

History: RFC-1945 (actual)

HTTP/1.1

This is the most used HTTP version. History: RFC-2068 (obsolete), RFC-2616 (obsolete), RFC-7230 (actual)

HTTP/2

According to W3Techs, as of March 2019, 33.9% of the top 10 million websites supported HTTP/2.

History: RFC-7540 (actual)

HTTP/3

Also called *HTTP-over-QUIC*, it is the upcoming major version of HTTP.

About MIME types

The Accept and Conten t-Type headers use *MIME types* to specify the type of message content.

There are basic MIME types for simple files and web formats: text/plain, text/htm l, applic ati on/xml, applic ati o n/json, applic ati on/ oct et- st ream, text/css, text/j ava script...



By SandRock cheatography.com/sandrock/

About MIME types (cont)

There are MIME types for all known file

formats: image/jpeg, image/png, audio/m
peg, applic ati on/pdf, applic ati o
n/zip, font/woff, video/mp4...

There are specific MIME types related to browsers and APIs: multip art /mixed, multip art /fo rm-data, multip art /b y ter anges, applic ati on/ x-w ww-for m-u rle ncoded...

Sometimes, extra information are added to a type. Text format can have a charset specification: text/p lai n;c har set =UTF-8 See: RFC-2045, RFC-2046, RFC-2047, RFC-4288, RFC-4289, RFC-2049; and MDN: MIME type.

Examples:

Conten t-Type: text/p lai n;c ha
r set =utf-8

Proxy

HTTP Proxy servers are act as an intermediary for client-to-server requests such as HTTP.

A forward proxy is a type of proxy server that receives and forwards requests in order to cache and facilitate access to a wide range of web servers.

A reverse proxy is a type of proxy server that receives and forwards requests in order to do load-balancing for a group of web servers.

See Proxy servers

Published 19th March, 2019. Last updated 19th March, 2019. Page 3 of 3. Sponsored by Readable.com Measure your website readability! https://readable.com