

ggalluvial Cheat Sheet

by seleven via cheatography.com/139867/cs/29584/

GGALLUVIAL ---- Cheatsheet

Introduction to ggalluvial

The **ggalluvial** package is a ggplot2 extension for producing alluvial plots.

Alluvial plots use variable-width ribbons and stacked bar plots to represent multi-dimensional or repeated-measures data with categorical or ordinal variables.

There are two types of alluvial format: Alluvial (Wide) Format & Lodes (Long) Format

More information

https://cran.r-project.org/web/packages/gg-alluvial/ggalluvial.pdf

Five Essential Components	Five	Essential	Comp	onents
---------------------------	------	------------------	------	--------

1 IVO EGGGIIdai (30poriorito
1. AIXS	A dimension (variable) along which the data are vertically grouped at a fixed horizontal position.
2. ALLUVIUM	Horizontal (x-) splines called alluvia span the width of the plot.
3. STRATUM	The groups at each axis are depicted as opaque blocks called strata.
4. LODE	The alluvia intersect the strata at lodes.
5. FLOW	The segments of the alluvia between pairs of adjacent axes are flows.

Basic Alluvial Wide Format		
Discription	Example	
load packages	library(ggalluvial)	
basic ggplot	gg <- ggplot(as.data.frame (UCBAdmissions), aes(y = Freq, axis1 = Gender, axis2 = Dept, axis3 = Admit))	
add alluvium	+ geom_alluvium()	
add stratum	+ geom_stratum()	
add text	+ geom_text(stat = "stratu- m", aes(label = paste(afte- r_stat(stratum))))	
add title	+ ggtitle("UC Berkeley admissions and rejection- s")	


The dataset "UCBAdmissions" is an aggregate data on applicants to graduate school at Berkeley for the six largest departments in 1973 classified by admission and sex.

It is a **3-dimensional array** resulting from cross-tabulating 4526 observations on 3 variables.

No Name Levels

- 1 Admit Admitted, Rejected
- 2 Gender Male, Female
- 3 Dept A, B, C, D, E, F


Graph of Wide Format



Change Color		
the border of alluvium	geom_alluvium(color="red")	
the border of stratum	geom_stratum(color="blue")	
the fill of alluvium	geom_alluvium(aes(fill=Dept)) geom_alluvium(aes(fill=Gender)) geom_stratum(aes(fill=Admit))	
the fill of stratum	geom_stratum(aes(fill=Dept)) geom_stratum(aes(fill=Gender)) geom_stratum(aes(fill=Admit))	

Setting the different fills of alluvium and stratum can help analysts easily analyze the data from different aspects.

Graph after changing Color & Fill by Dept



If using "fill=Dept", it means we are using colors grouped by each department.

It can help analyst to see the formation of each department: how many males and females in each department.

Also it shows how many people in each department are admitted and rejected.

|C|

By **seleven** cheatography.com/seleven/


Published 29th October, 2021. Last updated 29th October, 2021. Page 1 of 3. Sponsored by **ApolloPad.com**Everyone has a novel in them. Finish Yours!
https://apollopad.com



ggalluvial Cheat Sheet

by seleven via cheatography.com/139867/cs/29584/


Graph after changing Color & Fill by Gender



If using "fill=Gender", it means we are using colors grouped by different gender.

It can help analyst to see how many males and females apply for each department and finally admitted or rejected.

Graph after changing Color & Fill by Admit




If using "fill=Admit", it means we are using colors grouped by admitted or rejected. It can help analyst to see the formation admitted students: how many admitted students are from each department and of different gender.


Change Width

the width of alluvium	geom_alluvium(color="red"
	aes(fill=Dept),width=1/12)
the width of stratum	geom_stratum(color="blue"
	aes(fill=Dept),width=1/12)

Graph after changing Width



geom_alluvium vs geom_flow




The graph is using **geom_flow**.

We can see the difference between **geom_alluvium** and **geom_flow**.

After we use "flow", all males apply.

After we use "flow", all males apply for department A came together, which is also the same as other departments. It makes the graph much clearer than before since there is less cross alluviums between each axises.

Flip Coordinates




Adding coord_flip()

Flip cartesian coordinates so that horizontal becomes vertical, and vertical, horizontal. This is primarily useful for converting geoms and statistics which display y conditional on x, to x conditional on y.

More coding help

Description	Example
Adding the	+scale_x_discrete(limits =
names of	c("Gender", "Dept", "Admi-
each axis	t"))
Changing the	+scale_fill_brewer(type =
fill of stratum	"qual", palette = "Set1")

Adding lode



Adding geom_lode()

Basic Lodes (Long) Format

Descri- ption	Example
Convert data to Lodes format	to_lodes_form(as.data.frame- (UCBAdmissions),axes = 1:3,id = "Cohort")
load data	data(majors) majors\$curriculum <- as.factor(majors\$curriculum)

C

By **seleven** cheatography.com/seleven/

Published 29th October, 2021. Last updated 29th October, 2021. Page 2 of 3. Sponsored by **ApolloPad.com**Everyone has a novel in them. Finish

Yours!

https://apollopad.com



ggalluvial Cheat Sheet

by seleven via cheatography.com/139867/cs/29584/

Basic Lodes (Long) Format (cont)

basic ggplot ggplot(majors,aes(x =

semester, stratum = curriculum, alluvium = student,fill = curriculum, label = curric-

ulum))

add flow +geom_flow(stat = "alluvi-

um", lode.guidance = "frontb-

ack",color = "darkgray") +

add stratum +geom_stratum()

add title +ggtitle("student curricula

across several semesters")

The long format requires an additional indexing column that links the rows corresponding to a common cohort.


The data follows the major curricula of 10 students across 8 academic semesters.

Missing values indicate undeclared majors.

A data frame with 80 rows and 3 variables:

- 1. student: student identifier
- 2. semester: character tag for odd-numbered semesters
- 3. curriculum: declared major program

Graph of Lodes Format



This graph clearly shows a set of students' academic curricula over the course of several semesters.

The lode format gives us the option to aggregate the flows between adjacent axes, which may be appropriate when the transitions between adjacent axes are of primary importance.



By **seleven** cheatography.com/seleven/

Published 29th October, 2021. Last updated 29th October, 2021. Page 3 of 3. Sponsored by **ApolloPad.com**Everyone has a novel in them. Finish
Yours!
https://apollopad.com