

### General

```
var express = require('express');  
  
var app = express();
```

### Application

```
app.locals.title / strftime / email  
app.all(path, callback)  
app.use([path], callback)  
app.get(path, callback)  
app.post(path, callback)  
app.put(path, callback)  
app.delete(path, callback)  
app.enable(name) : Set to True  
app.disable(name) : Set to False  
app.enabled(name) : True if name is True  
app.disabled(name) : True if name is False  
app.engine(ext, callback)  
app.listen(path, callback)  
app.param([name], callback)  
app.render(view, [locals], callback)  
app.route(path)  
app.set(name, value)  
app.get(name)
```

### Request properties

```
req.baseUrl  
req.path  
req.originalUrl : req.baseUrl + req.path  
req.body : Require MW body-parser & multer  
req.cookies : Require MV cookie-parser  
req.signedCookies : Require MV cookie-parser  
req.fresh  
req.stale  
req.hostname  
req.ip : X-Forwarded-For  
req.method GET / POST / PUT / DELETE ...  
req.params Properties named route parameters  
req.protocol  
req.query  
req.route  
req.secure : TLS connection  
req.sockets  
req.xhr : X-Requested-With
```

### Request methods

### Response properties

### Response methods



By Maciev (shengti)  
[cheatography.com/shengti/](https://cheatography.com/shengti/)

Not published yet.  
Last updated 5th September, 2017.  
Page 1 of 1.

Sponsored by [Readable.com](https://readable.com)  
Measure your website readability!  
<https://readable.com>