

### General

```
var express = require('express');  
var app = express();
```

### Application

```
app.locals.title / strftime / email
```

```
app.all(path, callback)
```

```
app.use([path], callback)
```

```
app.get(path, callback)
```

```
app.post(path, callback)
```

```
app.put(path, callback)
```

```
app.delete(path, callback)
```

```
app.enable(name) : Set to True
```

```
app.disable(name) : Set to False
```

```
app.enabled(name) : True if name is True
```

```
app.disabled(name) : True if name is  
False
```

```
app.engine(ext, callback)
```

```
app.listen(path, callback)
```

```
app.param([name], callback)
```

```
app.render(view, [locals],  
callback)
```

```
app.route(path)
```

```
app.set(name, value)
```

```
app.get(name)
```

### Request properties

```
req.baseUrl
```

```
req.path
```

```
req.originalUrl: req.baseUrl + req.path
```

```
req.body : Require MW body-parser &  
multer
```

```
req.cookies : Require MV cookie-parser
```

```
req.signedCookies : Require MV cookie-  
parser
```

```
req.fresh
```

```
req.stale
```

```
req.hostname
```

```
req.ip : X-Forwarded-For
```

```
req.method GET / POST / PUT / DELETE ...
```

```
req.params Properties named route  
parameters
```

```
req.protocol
```

```
req.query
```

```
req.route
```

```
req.secure : TLS connection
```

```
req.subdomains
```

```
req.xhr : X-Requested-With
```

### Request methods

### Response properties

### Response methods



By **Maciev** (shengti)  
[cheatography.com/shengti/](https://cheatography.com/shengti/)

Not published yet.  
Last updated 5th September, 2017.  
Page 1 of 1.

Sponsored by **Readability-Score.com**  
Measure your website readability!  
<https://readability-score.com>