cmppDB

方法	参数	类型
keyExist	(String)	boolean
remove	(String)	boolean
get	(String)	Object
put	(String, Object)	boolean
getBytes	(String)	byte[]
getString	(String)	string

bytes, class, cmppDBService, equals, getClass, hashCode, ikvDBClient, init, notify, notifyAll, prefix, setCmppDBService, setIkvDBClient, setPrefix, string, toString, wait

db

方法	参数	类型
executeInsertReturnID	()	
executeInsertReturnID	()	
executeFirstSelectSQL	()	
executeFirstSelectSQL	()	
executeSelectSQL	()	
executeSelectSQL	()	
executeUpdateSQL	()	
executeUpdateSQL	()	
executeUpdateSQL	()	
executeSelectSQLWithAuth	()	
executeSelectSQLWithAuth	()	
executeUpdateSQLWithAuth	(String, String, String, String, String[])	boolean
executeUpdateSQLWithAuth	(String, String, String, String[])	boolean
executeUpdateSQLWithAuth	(String, String, String, String)	boolean
executeInsertSQLWithAuth	()	
getResultJson	()	

coder

方法	参数	类型
urlEncode	(String, String)	String
sha1	(String)	String
base64Decode	(String, String)	String
base64Decode	(String)	byte[]
crc32Encode	(String)	Long
hmac_sha1	(String, String)	String
md5Encode	(String)	String
urlDecode	(String, String)	String
base64Encode	(String)	String
escape	(String)	String
unescape	(String)	String

getClass, equals, class, hashCode, init, wait, notify, toString, notifyAll

By Prankster (szh214)
cheatography.com/szh214/
zhso.net/

Published 24th June, 2015.
Last updated 11th May, 2016.
Page 1 of 1.

Sponsored by Readable.com
Measure your website readability!
https://readable.com