

SSH configuration

configure terminal

hostname SW1	hostname definition
ip domain name test.local	domain name definition
crypto key generate rsa	choose a minimum 1024 key length

ip ssh version 2

username <name> secret <password>	user and password for SSH access
line vty 0 4	select lines with SSH access
transport input telnet ssh	
login local	

switchport security

configure terminal

interface interface_name	choose interface for setting security
---------------------------------	---------------------------------------

switchport mode access	security only available in mode access
-------------------------------	--

switchport port-security ?	list of available options
-----------------------------------	---------------------------

aging

mac-address

maximum

violation

switchport port-security maximum 1	only 1 permitted device
---	-------------------------

switchport port-security mac-address ?	list of available options
---	---------------------------

H.H.H allowed device mac-address

forbidden denied device mac-address

sticky memorize current connected device

switchport port-security violation ?	list of available options
---	---------------------------

protect does not allow

restrict does not allow and log violation

shutdown does not allow and turns off port

switchport port-security	to activate after setting security
---------------------------------	------------------------------------

switchport security (cont)

shutdown && no shutdown	The only way to restart a shutdown port
--	---

show mac address-table	display of MACs memorized by switch. MACs are erased if they do not send packages for more than 5 minutes
-------------------------------	---

show port-security	general display of port security settings
---------------------------	---

show port-security interface e0/0	detailed display of a specific port's security
--	--

show port-security address	show MACs memorized in security mode
-----------------------------------	--------------------------------------

copy run start	to make memorized MACs permanent between switch restarts
-----------------------	--

