

### Controller Services

DebuggerService

ModulesService

InterceptorService

ExceptionHandler

PluginService

HandlerService

RequestService

### Security Interceptor Property

useRegex [boolean=true]

rulesSource [string=xml, db, ioc, ocm, model]

queryChecks [boolean=true]

preEventSecurity [boolean=false]

validator [classpath]

validatorIOC [bean name]

validatorModel [model name]

### SES Interceptor Properties

configFile relative or absolute routes file  
defaults to (config/Routes.cfm)

### Coldbox Interception Points

afterConfigurationLoad()

afterAspectsLoad()

afterPluginCreation() \*

▶ pluginPath, custom, oPlugin

afterHandlerCreation() \*

▶ handlerPath, oHandler

afterModelCreation() \*

▶ modelName, oModel

applicationStart()

applicationEnd()

### Coldbox Interception Points (cont)

onInvalidEvent()

▶ invalidEvent, override, ehBean

onException() \*

▶ exception

onReinit()

preProcess()

postProcess()

preEvent()

▶ processedEvent

preLayout()

preProxyResults()

preRender() \*

▶ renderedContent

postEvent() \*

▶ processedEvent

postRender()

preViewRender()

▶ View, cache, cacheTimeout, cacheLast-  
AccessTimeout, cacheSuffix, module

postViewRender()

▶ View, cache, cacheTimeout, cacheLast-  
AccessTimeout, cacheSuffix, module,

renderedView

sessionStart()

sessionEnd()

\* Has intercept data

### Sample Plugin

```
component{
    function init(){
        set Plugin -
        Name(" MyP lug in");
        set Plugin -
        Ver sio n(" 1.0");
        set Plugin -
        Des cri pti on("My Plu gin");
        set Plugin -
        Aut hor ("Y our Name");
        set Plugin -
        Aut hor URL ("w ww.m y.c om");
    }
}
```

### Sample Interceptor

```
component{
    function configure(){
        //c onf igure
        properties here
    }
    //m ethod = interc -
    eption point
    function prePro ces -
    s(i nte rce ptD ata ,ev ent){
    }
}
```

### Framework Supertype

\$abort(), \$dump(), \$htmlhead(),  
\$include(), \$throw(), \$rethrow()  
addAsset(assetList)  
announceInterception(state, [interceptData])  
getColdBoxOCM([cachename])  
getController()  
getDatasource(alias)  
getDebugMode()  
getfwLocale()  
getInterceptor(name)  
getModel(name, [dsl], [initArguments])  
getMailSettings()  
getMailService()  
getNewMail()  
getMyPlugin(plugin, [newInstance])  
getPlugin(plugin, [customPlugin], [newIn-  
stance])  
getResource(resource, [default], [locale])  
getSetting(name, [fwSetting])  
getSettingsBean()  
getSettingStructure([fwSetting], [DeepC-  
opyFlag])  
includeUDF(udfLibrary)  
persistVariables(persist, [persistStruct])  
populateModel(model, scope, trustedSetter,  
include, exclude)  
renderExternalView(view)



By TheNewCoke  
(TheNewCoke)

[cheatography.com/thenewcoke/](http://cheatography.com/thenewcoke/)

Not published yet.

Last updated 12th May, 2016.

Page 1 of 4.

Sponsored by [CrosswordCheats.com](http://CrosswordCheats.com)

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>

### Framework Supertype (cont)

**renderLayout**(layout)  
**renderView**([view], [cache], [Timeout], [LastAccessTimeout])  
**runEvent**(event, [prepostExempt], [private])  
**setDebugMode**(mode)  
**setNextEvent**(event, [queryString], [addTo-ken], [persist], [persistStruct], [ssl], [baseURL], [postProcessExempt], [URL], [URI], [statusCode])  
**setSetting**(name, value)  
**setFWLocale**(locale)  
**settingExists**(name, [fwSetting])

### Interceptor Methods

**configure**()  
**getProperties**(properties)  
**setProperties**()  
**getProperty**(name)  
**setProperty**(name, value)  
**propertyExists**(name)  
**unregister**(state)  
**clearBuffer**()  
**appendToBuffer**(string)  
**getBufferString**()  
**getBufferObject**()

### Render Datatypes

json, jsonp, jsont, xml, pdf, wddx, text, plain, html

### Renderer Plugin

**renderView**(view, cache, cacheTimeout, cacheLastAccessTimeout, cacheSuffix, module, args, collection, collectionAs)  
**renderLayout**(layout, view, module, args)

### Cachebox Interception Points

**afterCacheElementInsert**()  
 ▶ Cache, cacheObject, cacheObjectKey, cacheObjectTimeout, cacheObjectLastAccessTimeout  
**afterCacheElementRemoved**()  
 ▶ Cache, cacheObjectKey  
**afterCacheElementExpired**()  
 ▶ Cache, cacheObjectKey  
**afterCacheElementUpdated**()  
 ▶ Cache, cacheNewObject, cacheOldObject  
**afterCacheClearAll**()  
 ▶ Cache  
**afterCacheRegistration**()  
 ▶ Cache  
**afterCacheRemoval**()  
 ▶ Cache (name)  
**beforeCacheRemoval**()  
 ▶ Cache  
**beforeCacheReplacement**()  
 ▶ oldCache, newCache  
**afterCacheFactoryConfiguration**()  
 ▶ cacheFactory  
**beforeCacheFactoryShutdown**()  
 ▶ cacheFactory  
**afterCacheFactoryShutdown**()  
 ▶ cacheFactory  
**beforeCacheShutdown**()  
 ▶ cache  
**afterCacheShutdown**()  
 ▶ Cache

### Request Context Common Methods

**buildLink**(linkto, [translate], [ssl], [baseURL], [queryString])  
**clearCollection**()  
**collectionAppend**(collection, [overwrite])  
**getCollection**([DeepCopyFlag], [private])  
**getCurrentAction**()  
**getCurrentEvent**()  
**getCurrentHandler**()  
**getCurrentLayout**()  
**getCurrentModule**()

### Request Context Common Methods (cont)

**getCurrentRoute**()  
**getCurrentRoutedURL**()  
**getCurrentView**()  
**getDefaultLayout**()  
**getDefaultView**()  
**getEventName**()  
**getHTTPHeader**(header, [default])  
**getHTTPMethod**()  
**getModuleRoot**()  
**getSESBaseURL**()  
**setSESBaseURL**()  
**getSize**()  
**getTrimValue**(name, [default], [private])  
**getValue**(name, [default], [private])  
**isAjax**()  
**isProxyRequest**()  
**isSES**()  
**isSSL**()  
**noExecution**()  
**noRender**([remove])  
**overrideEvent**(event)  
**paramValue**(name, value, [private])  
**renderData**( type, data, [contentType], [encoding], [statusCode], [statusText], [jsonCase], [jsonQueryFormat], [jsonAsText], [xmlColumnList], [xmlUseCDATA], xmlListDelimiter], [xmlRootName])  
**removeValue**(name, [private])  
**setHTTPHeader**(statusCode, statusText, name, value, charset)  
**setLayout**(name)  
**setValue**(name, value, [private])  
**setView**(name, [noLayout], [cache], [cacheTimeout], [cacheLastAccessTimeout], [cacheSuffix], [layout])



By **TheNewCoke**  
 (TheNewCoke)

[cheatography.com/thenewcoke/](http://cheatography.com/thenewcoke/)

Not published yet.  
 Last updated 12th May, 2016.  
 Page 2 of 4.

Sponsored by **CrosswordCheats.com**  
 Learn to solve cryptic crosswords!  
<http://crosswordcheats.com>

### Request Context Common Methods (cont)

`valueExists(name, [private])`  
`showDebugPanel(boolea`

Received as `event` to event handlers

### Controller Common Methods

`getAppRootPath()`  
`getCacheBox()`  
`getLogBox()`  
`getWireBox()`  
`getColdboxOCM([name])`  
`getColdboxSettings()`  
`getConfigSettings()`  
`getPlugin(plugin, [customPlugin], [newInstance])`  
`get{ServiceName}()`  
`getSettingStructure([fwSetting], [DeepCopy-Flag])`  
`getSetting(name, [fwSetting])`  
`persistVariables(persist, [persistStruct])`  
`runEvent(event, [prepostExempt], [private])`  
`settingExists(name, [fwSetting])`  
`setSetting(name, value)`  
`setNextEvent(event, [queryString], [addTo-ken], [persist], [persistStruct], [ssl], [baseUrl], [postProcessExempt], [URL], [URI], [statusCode])`

### Sample Handler Code

```
component{
    any function index( event, rc, prc ){
        return "Hello";
    }
}
```

### URL Actions (index.cfm?)

`fwreinit=1` or `{reinitPassword}`  
`debugmode=true`  
`debugpass={DebugPass}`  
`fwcache=anything`

### ColdBox Config

Coldbox (struct)  
 Settings (struct)  
 Conventions (struct)  
 Environments (struct)  
 loc (struct)  
 WireBox (struct)  
 Debugger (struct)  
 mailSettings (struct)  
 l18n (struct)  
 Webservices (struct)  
 Datasources (struct)  
 LayoutSettings (struct)  
 Layouts (array of structs)  
 Cachebox (struct)  
 Logbox (struct)  
 InterceptorSettings (struct)  
 Interceptors (array of structs)  
 Modules (struct)  
 Flash (struct)  
 ORM (struct)  
 Validation (struct)

### Config Injected Vars

AppMapping  
 Controller  
 LogBoxConfig

### SES Route Methods


`addRoute(*)`  
`addModuleRoutes(pattern, module)`  
`setBaseUrl()`  
`setUniqueURLS()`  
`setAutoReload()`  
`setExtensionDetection()`  
`setValidExtensions()`  
`setThrowOnInvalidExtension()`  
`setLooseMatching()`

### addRoute()

[pattern]  
 [handler]  
 [action]  
 [matchVariables]  
 [view]  
 [viewNoLayout]  
 [valuePairTranslation]  
 [constraints]  
 [module]

### SES Routes

Default Pattern :handler/:action?  
 :var ANY Placeholder  
 :var-numeric Numeric  
 :var-alpha Alpha  
 :var{X} Limit by X  
 ? = optional placeholder  
 :regex() Limit by regex  
 Valid Extensions: xml, json, jsont, html, htm, rss



By **TheNewCoke**  
 (TheNewCoke)

[cheatography.com/thenewcoke/](http://cheatography.com/thenewcoke/)

Not published yet.  
 Last updated 12th May, 2016.  
 Page 3 of 4.

Sponsored by **CrosswordCheats.com**  
 Learn to solve cryptic crosswords!  
<http://crosswordcheats.com>

### Folder Conventions

Application.cfc  
index.cfm (empty)  
config  
    ▶ Coldbox.cfc  
    ▶ Routes.cfm  
handlers  
model  
modules  
layouts  
views

### Implicit Handler Events

preHandler,pre{Action}  
postHandler,post{Action}  
aroundHandler  
around{Action}  
onMissingAction

### Handler Properties

This scope properties  
event\_cache\_suffix  
preHandler\_only  
preHandler\_except  
postHandler\_only  
postHandler\_except  
allowedMethods

### Core Interceptors

Security  
SES

### Core Plugins

AntiSamy	Logger
ApplicationStorage	MailService
ClientStorage	MessageBox
ClusterStorage	ORMService

### Core Plugins (cont)

CookieStorage	QueryHelper
DateUtils	Renderer
FeedGenerator	ResourceBundle
FeedReader	SessionStorage
FileUtils	Timer
i18n	Utilities
IOC	Validator
JavaLoader	Webservices
JSON	XMLConverter
JVMUtils	Zip



By **TheNewCoke**  
(TheNewCoke)

[cheatography.com/thenewcoke/](http://cheatography.com/thenewcoke/)

Not published yet.  
Last updated 12th May, 2016.  
Page 4 of 4.

Sponsored by **CrosswordCheats.com**  
Learn to solve cryptic crosswords!  
<http://crosswordcheats.com>