

by Thissitesucks via cheatography.com/141008/cs/30120/

Basics	
h	Move left
j	Move down
k	Move up
I	Move right
i	Insert mode
jj	Normal mode
gh	Mouse hover
{count}{motion} Repeat {motion} {count} times	

Word Movement		
w	Jump to the beginning of the next word	
W	Jump to the beginning of the next WORD	
е	Jump to the end of the next word	
E	Jump to the end of the next WORD	
b	Jump to the beginning of the previous word	
В	Jump to the beginning of the previous WORD	
ge	Jump to the end of the previous word	
gE	Jump to the end of the previous WORD	

Horizontal Movement		
0	Jump to the start of the line	
\$	Jump to the end of the line	
_	Jump to the first non-blank character of a line	
g_	Jump to the last non-blank character of a line	

Insert Mode	
i	Insert before cursor
1	Insert at the beginning of the line
a	Insert (append) after the cursor
Α	Insert (append) at the end of the line
0	Insert a new line below the current line
О	Insert a new line above the current line
ea	Insert (append) at the end of the word
Ctrl + h	Delete character before the cursor during insert mode
Ctrl + w	Delete word before the cursor during insert mode
gi	Go to last place you left insert mode
jj	Exit insert mode

Vertical Movement		
gg	Go to the first line of the document	
G	Go to the last line of the document	
{line}gg	Go to {line}	
}	Jump to next paragraph	
{	Jump to previous paragraph	
)	Jump to next sentence	
(Jump to previous sentence	
%	Jump to matching (), [], {}	
gd	Go to definition	
gD	Open definition aside	
gf	Go to file under the cursor	
Н	Jump to top of screen	
М	Jump to middle of screen	
L	Jump to bottom of screen	
Ctrl + e	Move screen down one line	
Ctrl + y	Move screen up one line	
Ctrl + d	Jump forward 1/2 a screen	
Ctrl + u	Jump back 1/2 a screen	

Visual Mode	
٧	Go into character-wise visual mode
V	Go into line-wise visual mode
Ctrl + v	Go into block-wise visual mode
aw	Select a word
iw	Select inner word
ab	Select a block with ()
ib	Select inner block with ()
аВ	Select a block with {}
iB	Select inner block with {}
at	Select a block with <> tags
it	Select inner block with <> tags



By Thissitesucks

Not published yet. Last updated 26th October, 2023. Page 1 of 4. Sponsored by **Readable.com**Measure your website readability!
https://readable.com



by Thissitesucks via cheatography.com/141008/cs/30120/

Visual Mode (cont)	
0	Move to other end of marked area
0	Move to other corner of block
У	Yank selected text
d	Delete marked text
u	Changed selected text to lowercase
U	Changed selected text to uppercase
af	Select increasingly bigger blocks of text
gb	Adds an additional cursor
{motion}{operator} In visual mode first you specify the motion to select text and then you apply the operator	

Vim Surround	
ds{existing}	Delete {existing} surround
cs{existing}{de- sired}	Change {existing} surround to {desired}
ys{motion}{d- esired}	Add {desired} surround to text defined by {motion}
S{desired}	Surround selection when in visual mode

VSCode Keybindings		
Ctrl + p	Open command palette	
>	List every command	
@	List every local symbol	
Ctrl + Shift + .	Open local symbol list	
#	List every global symbol	
Ctrl + Shift + ñ	Create new terminal	
Ctrl + ñ	Toggle terminal	
Ctrl + PageDown	Focus next terminal group	
Ctrl + PageUp	Focus previous terminal group	
Alt + DownArrow	Focus next terminal in group	
Alt + UpArrow	Focus previous terminal in group	

Tabs	
gt	Move to next tab
gT	Move to previous tab
{number}gt	Move to tab {number}
<leader>tt</leader>	Create new tab
<leader>tc</leader>	Close tab
<leader>to</leader>	Close all tabs but the current one
<leader>tl</leader>	Move tab to the right
<leader>th</leader>	Move tab to the left
<leader>tn</leader>	Move the tab to the group on the right
<leader>tp</leader>	Move the tab to the group on the left
<leader>te</leader>	Even tabs widths

Editing	
r	Replace a single character
R	Replace until ESC is pressed
x	Delete a character
X	Delete character before the cursor
s	Delete character and substitute text
d	Delete up to {motion}
dd	Delete line
<leader>dd</leader>	Delete to void
D	Delete to the end of the line
С	Change up to {motion}
СС	Change a line
С	Change to the end of the line
У	Yank (copy) {motion}
уу	Yank a line
Υ	Yank a line. (= yy)
р	Paste
P	Paste before the cursor
~	Switch case
g~	Switch case up to {motion}
g~~	Switch case of a line
gu	Switch to lowercase up to {motion}
gU	Switch to uppercase up to {motion}
>	Shift text right



By Thissitesucks

Not published yet. Last updated 26th October, 2023. Page 2 of 4. Sponsored by **Readable.com**Measure your website readability!
https://readable.com



by Thissitesucks via cheatography.com/141008/cs/30120/

Editing (cont)	
<	Shift text left
<leader>j</leader>	Join lines
gcc	Toggle line comment
gC	Toggle block comment
уур	Duplicate line
ddp	Swap lines
хр	Swap characters
=	Format
	Repeat last command
{operator}{count}{motion} Apply {operator} on {motion}	

Search	
/{pattern}	Search for {pattern}
?{pattern}	Search for {pattern} backwards
1	Repeat last search forwards
?	Repeat last search backwards
n	Go to next match
N	Go to previous match
{operator}gn	Apply {operator} on next match
Ctrl + n	Clear highlighted text
{pattern} is a regex	

Find Character	
f{character}	Jump to next occurrence of {character}
F{character}	Jump to previous occurrence of {character}
t{character}	Jump to before next occurrence of {character}
T{character}	Jump to after previous occurrence of {character}
•	Repeat previous f, t, F or T
,	Repeat previous f, t, F or T backwards

Vim Easymotion	
<leader><leader>w</leader></leader>	Start of words
<leader><leader>b</leader></leader>	Start of words backwards
<leader><leader>bdw</leader></leader>	Start of words everywhere
<leader><leader>e</leader></leader>	End of words
<leader><leader>ge</leader></leader>	End of words backwards
<leader><leader>deader>bde</leader></leader>	End of words everywhere
<leader><leader>j</leader></leader>	Beginning of lines
<leader><leader>k</leader></leader>	Beginning of lines backwards
<leader><leader>f{character}</leader></leader>	Find {character}
<leader><leader>F{character}</leader></leader>	Find {character} backwards
<leader><leader>t{character}</leader></leader>	Until (character)
<leader><leader>T{character}</leader></leader>	Until (character) backwards
<leader><leader>s{character}</leader></leader>	Search {character} everywhere

Text Objects	
diw	Delete inner word
daw	Delete a word
dis	Delete inner sentence
das	Delete a sentence
dip	Delete inner paragraph
dap	Delete a paragraph
dib	Delete inside parentheses
dab	Delete text and parentheses
diB	Delete inside braces
daB	Delete text and braces
di[Delete inside brackets
da[Delete text and brackets
di"	Delete inside quotes
da"	Delete text and quotes
dit	Delete inside tag
dat	Delete text and tag

{operator}a{text-object} Apply operator to all {text-object} including
space after o before it
{operator}i{text-object} Apply operator to {text-object}
'dib' = 'di(' | 'diB' = 'di{'
Can be use with other operators (E.g: ciw)

C

By Thissitesucks

Not published yet.

Last updated 26th October, 2023.

Page 3 of 4.

Sponsored by **Readable.com**Measure your website readability!
https://readable.com



by Thissitesucks via cheatography.com/141008/cs/30120/

Folding	
zf{count}j	Create a fold from the cursor down {count} lines
zf/{pattern}	Create a fold from the cursor to {pattern}
za	Toggle fold at the cursor
ZO	Open fold under cursor
zO	Open all folds
ZC	Close fold under cursor
zM	Close all folds
zd	Delete fold at the cursor
zE	Delete all folds

Split Windows	
Ctrl-w + s	Open same file in a horizontal split
Ctrl-w + v	Open same file in a vertical split
Ctrl + h	Move to the window on the left
Ctrl + j	Move to the window below
Ctrl + k	Move to the window above
Ctrl + I	Move to the window on the right

Undo and Redo	
u	Undo last change
Ctrl + R	Redo last undo
U	Undo last changed line



By Thissitesucks

Not published yet. Last updated 26th October, 2023. Page 4 of 4. Sponsored by **Readable.com**Measure your website readability!
https://readable.com