Cheatography

javascript Cheat Sheet
by Torvak via cheatography.com/32041/cs/9823/

DOM (Document Object Model) Document

FIND HTML ELEMENTS

document.getElementById(id)	ex:
document.getElementsByTagName(name)	ex: all elements
document.getElementsByClassName(name)	ex: returns array
document.querySelectorAll("p.intro")	
document.formName.inputName	ex: <form name="formName"><input name="inputName"></form>

CHANGE HTML ELEMENTS

element.innerHTML = new html content	ex: replace content here
element.attribute = new value	change the attribute value of an HTML elem
element.setAttribute(attribute, value)	change the attribute value of an HTML elem
element.style.property = new style	change the style of an HTML elem
element.src='"urlImg.png"	change value of <img src="source url">
element.value = 'value"	ex: <input value="new value">

Adding and deleteting elements

document.createElement(elem)	ex: document.create("button") creates <button></button>
document.removeChild(elem)	remove a html elem
document.appendChild(elem)	add en html elem

DOM (Document Object Model) Document (cont)

document.replaceChild(elem)	replace an html element ex: list.replaceChild(textNode, list.childNodes[0])
document.write(text)	white into html output stream

Arrays

Indexed arrays

var objectArray = ["Saab", Date.now, myFunction];	cars[0] returns "Saab"
var array = []	initialize empty array
var array = new array(40)	40 uninitialized elems!

Associative arrays

var person = {firstName:"John", lastName:"Doe", age:46};	person.lastName or person["lastName"] returns

Looping indexed arrays

for(var i = 0; i < arrayName.length; i++) { return arrayName[i]}

Looping associative arrays

for (var keyEtudiant in tabEtudiant) {print keyEtudiant+":"+tabEtudiant[keyEtudiant]}

Array methods

arrayName.toString()	convert array contents to string
arrayName.join(" seperator ")	same as above: elem1 *elem2* elem3
arrayName.pop()	removes last elem
arrayName.puh(elem)	add new element to end of array

Arrays (cont)

arrayName.shift()	removes first elem from array | returns value of arrayName[0]
arrayName.unshift(elem)	adds new elem to begining of array
arrayName.length	returns number of elems in array
elete arrayName[0]	changes first elem of array to undefined
arrayName.splice(position, numElems, elemToAdd1, elementToAdd2)	add nzw items to an array
arrayName.splice(startingPos,numElemesToDelete)	removes numberOfElems to delete starting from startingPos
var pets = catsArray.concat(dogArray);	joins two array together into one
elem.innerHTML = arrayName;	replaces HTML content of elem by string containing the elems of arrayName

Sorting arrays

arrayName.sort()	sorts elems from less important to most important
arrayName.reverse()	sorts most important to less important

By **Torvak**
cheatography.com/torvak/

Not published yet.
Last updated 12th March, 2017.

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
http://crosswordcheats.com