Cheatography

Ducky mecha mini Cheat Sheet by VirtuaLeech via cheatography.com/184678/cs/38560/

| Backlighting modes | | RGB LED Zone Customization Modes | |
|----------------------|---|--|---|
| Fn+Alt+T | Wave (Default) Color Cycle Rain Drop Ripple Random Reactive Reactive * Halo * | Fn+Alt+G | CM1 cycle: First step: Turn on user's customized zone and color. Second step: Turn on user's customized zone and color in breathe mode. Third step: Turn off CM1. |
| | Breathe * | Fn+Alt+B | CM2 cycle: See CM1 cycle |
| | 100% Full Backlit * Radar * Backlit off | Fn+Alt+ CapsLock (REC) | Press for 3 seconds until the G (CM1) and B (CM2) keys light up, choose the |
| Fn+Alt+J Fn+Alt+L | Decrease speed Increase speed | | layer for setting, press it again and start recording. |
| Fn+Alt+T | Hold for 3 seconds to turn off | CapsLock+Z | Adjust color red (R) |
| | all backlit | CapsLock+X | Adjust color green (G) |
| Fn+Alt+Z | Alt+XAdjust color green (G)Alt+Cbrightness.Alt+VAdjust color blue (B)Alt+brightness. | CapsLock+C | Adjust color blue (B), |
| Fn+Alt+X | | CapsLock+V | Erase all LED light |
| Fn+Alt+C Fn+Alt+V | | CapsLock+ Spacebar | Color palette |
| Fn+Alt+ Spacebar | | CapsLock+ LeftShift | REC over, finish recording |
| | | Recording steps: 1 Press Fn+Alt+CapLock 3 seconds, press G to set CM1 and press B to set CM2. 2 CapLock will display current LED color. Color can be adjusted by CapLoc- k+Z/X/C/V. After setting color, hitting any | |



By VirtuaLeech

cheatography.com/virtualeech/

key on the keyboard will set that key to the selected color. 3 Repeating the above steps 4 Press CapLock+LeftShift to finish

recording.

Not published yet. Last updated 5th May, 2023. Page 1 of 1.

Mouse mode Fn+W Mouse up Fn+A Mouse left Fn+S Mouse down Fn+D Mouse right Fn+Q Left moude button Fn+E Right mouse button Fn+R Scroll up Fn+F Scroll down

| Mechanical shaft debounce time | | | |
|--------------------------------|----------------|--|--|
| Fn+Alt+Y | 5ms | | |
| Fn+Alt+U | 10ms (default) | | |
| Fn+Alt+I | 15ms | | |
| Fn+Alt+O | 25ms | | |

• Hold the combine keys for 3 sec, the keyboard will flash 3 times to indicate the debounce time has been switched successfully.

• The method is to adjust the debounce time of the metal shrapnel in the mechanical shaft during the pressing process. The shorter the time, the sooner it can be triggered, but if the time is too short may cause misjudgement.

Sponsored by ApolloPad.com Everyone has a novel in them. Finish Yours! https://apollopad.com