

Contexts

<code>kubectl config get-contexts</code>	Show contexts
<code>kubectl config current-context</code>	Show current context
<code>kubectl config use-context <my-cluster-name></code>	Switch context to another cluster
<code>kubectl config set-context --current --namespace=<namespace></code>	Change namespace

Logs

<code>kubectl logs <pod></code>	Show logs (stdout) of a pod
<code>kubectl logs -l <label>=<value></code>	Show logs (stdout) of pods that match a label
<code>kubectl logs <pod> --previous</code>	Show logs of a previous instantiation of a container
<code>kubectl logs <pod> -c <container></code>	Show logs for a specific container in a pod (i.e. init container)
<code>kubectl logs -f <pod></code>	Following logs from a pod
<code>kubectl logs -f -l <label>=<value> --all-containers</code>	Follow all logs from a pod that match a label
<code>kubectl logs <pod> --v=<0:9></code>	Show logs with verbosity level of logs from 0 - 9

Services

<code>kubectl get services</code>	Get all services in the current namespace
<code>kubectl get service --all-namespaces</code>	Get services in all namespaces
<code>kubectl get service -o wide</code>	Get services with more details
<code>kubectl get service <service> -o yaml</code>	Get the yaml for a service
<code>kubectl describe service <service></code>	Inspect a service
<code>kubectl get service --show-labels</code>	Get service's labels
<code>kubectl get service -l <label>=<value></code>	Get services that match a label



By [zenolis \(zenolis\)](#)
cheatography.com/zenolis/

Not published yet.
Last updated 3rd November, 2022.
Page 1 of 1.

Sponsored by [ApolloPad.com](#)
Everyone has a novel in them. Finish Yours!
<https://apollopad.com>