

Closures

```
// Syntax
{ (parameters) -> return type in
    statements
}
```

1. Closures are self-contained blocks of functionality that can be passed around and used in your code.

Closures Syntax Optimizations

```
let names = ["Chris", "Alex", "Ewa", "Barry",
"Daniella"]
// 1
reversedNames = names.sorted(by: { (s1: String,
s2: String) -> Bool in
    return s1 > s2
})
// 2. Inferring Type From Context
reversedNames = names.sorted(by: { s1, s2 in
return s1 > s2 })
// 3. Implicit Returns from Single Expression
Closures
reversedNames = names.sorted(by: { s1, s2 in s1
> s2 })
// 4. Shorthand Argument Names
reversedNames = names.sorted(by: { $0 > $1 })
// 5. Operator Methods, operator (>) is a method
reversedNames = names.sorted(by: >)
// 6. Trailing Closures
reversedNames = names.sorted { $0 > $1 }
// function with only one argument
reversedNames = names.sorted { $0 > $1 }
```

1. A trailing closure is written after the function call's parentheses, even though it is still an argument to the function.

Escaping Closures

```
var completionHandler: (() -> Void) = []
func someFunction(withEscapingClosure handler: @escaping () -> Void) {
    completionHandler.append(handler)
}
func someFunction(withNonEscapingClosure closure: () -> Void) {
}
```

Escaping Closures (cont)

```
> closure()
}
class SomeClass {
    var x = 10
    func doSomething() {
        someFunctionWithEscapingClosure {
            self.x = 100
        }
        someFunctionWithNonEscapingClosure {
            x = 200
        }
    }
}
```

1. A closure is said to escape a function when the closure is passed as an argument to the function, but is called after the function returns.

2. Marking a closure with *@escaping* means you have to refer to self explicitly within the closure.


Autoclosures

```
var customersInLine = ["Chris", "Alex", "Ewa",
"Barry", "Daniella"]
func serve(customer: CustomerProvider:
@autoclosure () -> String) {
    print("Now serving \(customerProvider())!")
}
serve(customer: customersInLine.remove(at:
0))
```

1. An *autoclosure* is a closure that is automatically created to wrap an expression that's being passed as an argument to a function.

2. An autoclosure lets you delay evaluation.

Functions



1. Functions are self-contained chunks of code that perform a specific task.

Property

```
class SomeClass {
    // Type Property
    static var storedTypeProperty = "Some value."

    static var computedTypeProperty: Int {
        return 27
    }

    class var overrideableComputedTypeProperty: Int {
        return 107
    }

    // Lazy Stored Property
    lazy var view = UIView()

    // Stored Property
    let data = [String]()

    // Computed Property
    var id: Int = 0 {
        willSet {
            print("About to set \(newValue)")
        }
        didSet {
            print("Did set id to \(id), oldValue is \(oldValue)")
        }
    }

    var idStr: String {
        set {
            id = Int(idStr) ?? 0
        }
        get {
            return String(id)
        }
    }

    var desc: String {
        return "Readonly property."
    }
}
```

Property (cont)

```
> }
```

1. Computed properties must be declared with the `var` keyword, because their value is not fixed.
2. A lazy stored property is a property whose initial value is not calculated until the first time it is used.

Enumeration

```
/// Use enum
enum Planet {
    case mercury, venus, earth, mars, jupiter, saturn, uranus, neptune
}

var p = Planet.venus
p = .uranus

/// Iterating over Enumeration Cases
enum Beverage: CaseIterable {
    case coffee, tea, juice
}

let numberOfChoices = Beverage.allCases.count
print("\nNumber of choices beverages available ")

for beverage in Beverage.allCases {
    print(" beverage is \(beverage)")
}

/// Associated Values
enum Barcode {
    case upc(Int, Int, Int, Int)
    case qrCode(String)
}
```

1. An enumeration defines a common type for a group of related values and enables you to work with those values in a type-safe way within your code.
2. Conforming to the *CaseIterable* protocol makes an enum iterable.